

Paste Thermal Tube 200g

pro-POWER



Specifications:

| | |
|------------------------------|--|
| Potting Compound Type | : Silicone |
| Dispensing Method | : Tube |
| Chemical Colour | : White |
| Weight | : 200g |
| Conductivity | : 0.65W/m.K |
| Dielectric Strength | : 18V/m |
| Lubricant Applications | : Electrical / Electronics / Mechanical / Cables |
| Lubricant Type | : Paste |
| Operating Temperature | : -50°C to +180°C |
| Packaging | : 200g tube |
| Thermo-conductive Components | : Powdered Metal Oxides |
| Density @ 20°C | : 2g/cm ³ |
| Penetration | : 220-270 |

Description:

Silicone Heat Transfer Compound is a metal oxide filled silicone oil providing an extremely efficient and exceptionally thermally conductive compound which will operate over a wide temperature range.

Application:

Apply to the base and mounting studs of diodes, transistors, thyristors, heat sinks, silicone rectifiers and semi-conductors, power resistors and radiators.

Features:

- Excellent non-creep characteristics
- Wide operating temperature range with low evaporation weight loss
- Excellent thermal conductivity even at high temperatures
- Easy to handle, economic in use and low in toxicity

Part Number Table

| Description | Part Number |
|-------------------------|-------------|
| Paste Thermal 200g Tube | PPC115 |

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER