PLA+ 3D Filament For 3D Printers





Features

- · High rigidity, good glossiness
- Suitable for printing large models
- · Toughness is 10 times more than standard PLA
- No wiredrawing problem
- · No cracking problem

Specification

Print temperature : 205°C to 225°C

Bed temperature : 60°C to 80°C

Print speed : 30 to 90mm/s

Part Number Table

Description	Colour	Part Number
PLA+ Filament, 1.75mm, 1kg/roll	Black	MC002547
	Green	MC002548
	Grey	MC002549
	Orange	MC002550
	Red	MC002551
	Silver	MC002552
	Blue	MC002553
	White	MC002554
	Yellow	MC002555
	Gold	MC002556
	Brown	MC002557
	Light Blue	MC011450
	Peak Green	MC011451
	Purple	MC011452
	Pine Green	MC011453
	Skin	MC011454
	Light brown	MC011455
	Olive Green	MC011456
	Dark Blue	MC011457

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of Premier Farnell Limited 2019.

www.element14.com www.farnell.com www.newark.com

