



Benefit from More Than 35 Years of Experience

www.wago.com/relays-and-optocouplers

Series	Input Nominal Voltage	Limiting Continuous Current							AU					ANSI/ISA		Item Number																			
2042 Series (module width 10,4 ... 26 mm)																																			
	24 VDC	6 A	-40 ... +70 °C (-13 ... +158 °F)													2042-3004																			
		8 A															2042-3014																		
		5 A																2042-3024																	
		10 A																2042-3034																	
		8 A																2042-3044																	
		6 A																2042-3054																	
	24 ... 230 V AC/DC	8 A			1	1											2042-3064																		
		5 A			1	3											2042-3074																		
		5 A			2	2											2042-3084																		
		3 A				1											2042-3809																		
		5 A				2											2042-3819																		
		3 A	-40 ... +50 °C (-13 ... +122 °F)			4											2042-3829																		
		4 A															2042-3839																		
		5 A	-40 ... +70 °C (-13 ... +158 °F)														2042-3849																		
		6 A			1												2042-3859																		
		5 A			1	1											2042-3869																		
3 A	-40 ... +50 °C (-13 ... +122 °F)			1	3										2042-3879																				
3 A			2	2											2042-3889																				
857 Series, Timer Relays (module width 6 mm)																																			
	24 VDC	6 A	-25 ... +70 °C (-13 ... +158 °F)														857-604																		
																	857-640																		
																	857-642																		
859 Series (module width: 6 mm)																																			
	5 VDC	-40 ... +50 °C (-13 ... +122 °F)																859-302																	
	12 VDC																	859-312																	
	12 VAC/DC																	859-303																	
	24 VDC																	5 A	-40 ... +70 °C (-13 ... +158 °F)																859-353
																																			859-390
																																			859-392
																																			859-398
																																			859-304
																																			859-314
	24 VAC/DC																	859-354																	
	36 VDC																	3 A	-40 ... +50 °C (-13 ... +122 °F)															859-386	
	859-394																																		
	48 VDC																	5 A																859-397	
	48 VAC/DC																																	859-355	
	60 VAC/DC																																	859-356	
	72 VDC																																	859-393	
	110 VDC																	3 A	-40 ... +70 °C (-13 ... +158 °F)																859-399
																																			859-391
																																			859-317
																																			859-317
115 V AC/DC	5 A																859-360																		
115 VAC																	859-367																		
220 VDC																	859-318																		
230 V AC/DC																	859-358																		
230 VAC																	859-359																		
230 VAC																	859-368																		

0688-0192/0002-6901 - RELAIS Z-CARD 1 US - 01/2019
 Printed in Germany - Subject to changes
 WAGO is a registered trademark of WAGO Verbindungstechnik GmbH.
 Copyright - WAGO Verbindungstechnik GmbH & Co. KG - All rights reserved.
 The content and structure of the WAGO website, catalogs, videos and other WAGO
 media are subject to copyright. Distribution or modification of the contents of these
 pages and videos is prohibited. Furthermore, the content
 may neither be copied nor made available to third
 parties for commercial purposes. Any subject to copyright are the images and videos
 that were made available to WAGO Verbindungstechnik GmbH & Co. KG by third parties.

Series	Input Nominal Voltage	Limiting Continuous Current							AU					ANSI/ISA		Item Number
--------	-----------------------	-----------------------------	--	--	--	--	--	--	----	--	--	--	--	----------	--	-------------

857 Series (module width: 6 mm)

	24 ... 230 V AC/DC	6 A	-40 ... +70 °C (-13 ... +158 °F)														857-359	
	12 VDC																857-369	
	24 VDC	4 A	-40 ... +60 °C	2x1													857-303	
	24 VAC/DC																857-304	
	24 VAC/DC	6 A	-40 ... +60 °C														857-314	
	115 V AC/DC																857-1330	
	230 V AC/DC	6 A	-40 ... +60 °C															857-354
	230 VAC																	857-357
																	857-358	
																	857-358/006-000	
																	857-368/006-000	

788 Series (module width: 15 mm)

	12 VDC	8 A	-40 ... +70 °C (-13 ... +158 °F)															788-311		
		16 A																788-303		
	24 VDC	0.3 A	-40 ... +60 °C																788-353	
			8 A																-40 ... +70 °C (-13 ... +158 °F)	788-906*
		8 A	-40 ... +70 °C (-13 ... +158 °F)	2																788-312
			6 A																	-25 ... +70 °C (-13 ... +158 °F)
		8 A	-25 ... +70 °C (-13 ... +158 °F)	2																788-346
			8 A																	-40 ... +70 °C (-13 ... +158 °F)
		8 A	-40 ... +70 °C (-13 ... +158 °F)	1																788-390
			8 A																	-40 ... +70 °C (-13 ... +158 °F)
		16 A	-40 ... +70 °C (-13 ... +158 °F)	1																788-354
			16 A																	-40 ... +70 °C (-13 ... +158 °F)
		16 A	-40 ... +70 °C (-13 ... +158 °F)	1																788-404
			16 A																	-40 ... +70 °C (-13 ... +158 °F)
	8 A	-40 ... +70 °C (-13 ... +158 °F)	2																788-341	
		8 A																	-40 ... +70 °C (-13 ... +158 °F)	788-512
	16 A	-40 ... +70 °C (-13 ... +158 °F)	1																788-546	
		16 A																	-40 ... +70 °C (-13 ... +158 °F)	788-506
	8 A	-40 ... +70 °C (-13 ... +158 °F)	2																788-541	
		8 A																	-40 ... +70 °C (-13 ... +158 °F)	788-313
	16 A	-40 ... +70 °C (-13 ... +158 °F)	1																788-305	
		16 A																	-40 ... +70 °C (-13 ... +158 °F)	788-314
	8 A	-40 ... +70 °C (-13 ... +158 °F)	2																788-314	
		16 A																	-40 ... +70 °C (-13 ... +158 °F)	788-306
	8 A	-40 ... +70 °C (-13 ... +158 °F)	2																788-315	
		16 A																	-40 ... +70 °C (-13 ... +158 °F)	788-307
	8 A	-40 ... +70 °C (-13 ... +158 °F)	2																788-515	
		8 A																	-40 ... +70 °C (-13 ... +158 °F)	788-548
16 A	-40 ... +70 °C (-13 ... +158 °F)	1																788-615		
	16 A																	-40 ... +70 °C (-13 ... +158 °F)	788-507	
8 A	-40 ... +70 °C (-13 ... +158 °F)	2																788-607		
	8 A																	-40 ... +70 °C (-13 ... +158 °F)	788-543	
8 A	-40 ... +70 °C (-13 ... +158 °F)	2																788-516		
	8 A																	-40 ... +70 °C (-13 ... +158 °F)	788-616	
16 A	-40 ... +70 °C (-13 ... +158 °F)	1																788-549		
	16 A																	-40 ... +70 °C (-13 ... +158 °F)	788-508	
																		788-608		
																		788-544		

858 Series (module width: 31 mm)

	12 VDC	5 A	-25 ... +70 °C (-13 ... +158 °F)															858-303		
																		858-304		
	24 VDC	5 A	-25 ... +70 °C (-13 ... +158 °F)																858-314	
																			858-354	
		6 A	-40 ... +70 °C (-13 ... +158 °F)	2																858-355
																				12 A
	12 A	-40 ... +70 °C (-13 ... +158 °F)	2																858-324	
		12 A																	858-504	
	24 VAC	5 A	-25 ... +70 °C (-13 ... +158 °F)																858-514	
																			5 A	858-305
	48 VDC	12 A	-40 ... +55 °C (-13 ... +131 °F)																858-325	
																			5 A	858-307
	110 VDC	6 A	-40 ... +70 °C (-13 ... +158 °F)																858-392	
																			12 A	858-327
	12 A	-40 ... +55 °C (-13 ... +131 °F)	2																858-507	
		12 A																	858-517	
	115 VAC	5 A	-25 ... +70 °C (-13 ... +158 °F)																858-308	
																			5 A	858-391
	220 VDC	6 A	-40 ... +70 °C (-13 ... +158 °F)																858-328	
																			12 A	858-508
230 VAC	5 A	-25 ... +70 °C (-13 ... +158 °F)																858-518		
																		12 A	858-528	

*Force-guided contacts