



# Plug, SMA

## Solder, RG405/U




### Specifications:

Connector Type : SMA Coaxial  
 Body Style : Straight Plug  
 Coaxial Termination : Solder  
 Impedance : 50Ω  
 RG Cable Type : RG-405, 0.085" Semi-Rigid  
 Contact Plating : Gold  
 Bodies : Brass per JIS-C3604.  
 Centre Contact : Brass per JIS-C3604.  
 Insulation : PTFE per ASTM D1457 and ASTM D1710.  
 Connector interface per MIL-STD-348A. Part to be clean and free of burrs



Dimensions : Millimetres (Inches)

Description	Material	Finish
Shell	Brass	Gold 3μ" Min.
Gasket	Silicone	None
Washer	Stainless Steel	
Insulation	PTFE	
Body	Brass	Gold 3μ" Min.
Centre Contact		Gold 50μ" Min.



Stripping Dimension

### Part Number Table

Description	Part Number
Plug, SMA, Solder, RG405/U	19-55V-3-TGG

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

