ACW6M119012

PRESSOSTAT - WITH 0,07 TO 7,6 BARS - ACW6



Main

Range of product	OsiSense XM
Pressure sensor name	ACW
Pressure sensor type	Electromechanical pressure sensor
Product specific application	For regulation between 2 thresholds
Scale type	Adjustable differential
Contacts type and composition	1 C/O, snap action
Cable entry	1 entry tapped for ISO M20 cable gland
Fluid connection type	G 1/4 (female) conforming to ISO 228
Materials in contact with fluid	Phosphor bronze
Pressure sensor size	34 bar
Adjustable range of switching point on falling pressure	5.234 bar
Adjustable range of switching point on rising pressure	8.642.3 bar
Pressure actuator	Bellows
Electrical circuit type	Control circuit

Complementary

Electrical connection	Screw-clamp terminals, 1 x 12 x 2.5 mm ²	
Controlled fluid	Air (-73125 °C) Hydraulic oil (-73125 °C) Non-corrosive fluid (-73125 °C)	
Short-circuit protection	10 A by gG cartridge fuse	
Enclosure material	Zinc alloy	
Possible differential minimum at low setting	3.4 bar	
Possible differential minimum at high setting	3.4 bar	
Possible differential maximum at low setting	8.3 bar	
Possible differential maximum at high setting	8.3 bar	
Maximum permissible pressure - per cycle	140 bar	
Mechanical durability	1000000 cycles	
Setting	External	
Local display	Without	
Terminals description ISO n°1	(1-2)NC (3-4)NO	
Width	88 mm	
Height	221 mm	
Depth	68 mm	
Product weight	2.1 kg	,

Environment

protective treatment	TC	-
standards	CE EN/IEC 60947-5-1	
product certifications	CSA UL recognized EAC	
IP degree of protection	IP65 conforming to EN/IEC 60529	
ambient air temperature for operation	-5685 °C	

Offer Sustainability



Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be Compliant

