



### Main

Range of product	OsiSense XU
Series name	Application material handling
Electronic sensor type	Photo-electric sensor
Sensor name	XUE
Sensor design	Compact 90 x 90
Detection system	Reflex
Material	Plastic
Supply circuit type	DC
Wiring technique	5-wire
Discrete output type	PNP
Discrete output function	2 NO/NC programmable
Analogue output range	4...20 mA
Electrical connection	1 male connector M12, 5 pins
Product specific application	Distance measurement on reflector
Emission	Infrared laser, pulsed (class 1), wavelength: 905 nm conforming to IEC 600825-1 Red laser, pulsed (class 2), wavelength: 670 nm conforming to IEC 600825-1
[Sn] nominal sensing distance	30 m need reflector XUZC250

### Complementary

Enclosure material	ABS, anti-shock
Lens material	PMMA
Linearity	<= +/- 40 mm
Spot dimension	45 x 60 mm at 30 meters
Status LED	1 LED (green) for supply on 2 LEDs (yellow) for output 4 LEDs (red) for parametering 1 LED (orange) for slow mode
[Us] rated supply voltage	24 V DC with reverse polarity protection
Supply voltage limits	18...30 V DC
Switching capacity in mA	100 mA (overload and short-circuit protection)
Switching time	30 ms fast mode 65 ms slow mode
Voltage drop	<= 2.4 V (closed state)

Current consumption	125 mA (no-load)
Delay first up	30 ms 65 ms
Delay response	30 ms fast mode 65 ms slow mode
Setting-up	Parametering by buttons
Height	93 mm
Length	95 mm
Width	42 mm
Product weight	0.2 kg

## Environment

Product certifications	CE cULus
Ambient air temperature for operation	-10...50 °C
Ambient air temperature for storage	-40...80 °C
Vibration resistance	7 gn, amplitude = +/- 0.5 mm (f = 10...55 Hz) conforming to IEC 60947-5-2
Shock resistance	30 gn (duration = 11 ms) conforming to IEC 60947-5-2
IP degree of protection	IP67 conforming to IEC 60529

## Offer Sustainability

RoHS (date code: YYWW)	Will not be compliant Will not be compliant
------------------------	--

## Contractual warranty

Warranty period	18 months
-----------------	-----------