Product data sheet Characteristics

XUX1APANM12

photo-electric sensor - XUX - reflex - Sn 14m -12..24VDC - M12



Main

Man	
Range of product	OsiSense XU
Series name	General purpose single mode
Electronic sensor type	Photo-electric sensor
Sensor name	XUX
Sensor design	Compact 92 x 71
Detection system	Reflex
Material	Plastic
Type of output signal	Discrete
Supply circuit type	DC
Wiring technique	3-wire
Discrete output type	PNP
Discrete output function	1 NO
Electrical connection	1 male connector M12, 4 pins
Product specific application	-
Emission	Infrared reflex
[Sn] nominal sensing distance	14 m reflex need reflector XUZC50

Complementary

Range of product	OsiSense XU	
Series name	General purpose single mode	
Electronic sensor type	Photo-electric sensor	
Sensor name	XUX	
Sensor design	Compact 92 x 71	
Detection system	Reflex	
Material	Plastic	
Type of output signal	Discrete	
Supply circuit type	DC	
Wiring technique	3-wire	
Discrete output type	PNP	
Discrete output function	1 NO	
Electrical connection	1 male connector M12, 4 pins	
Product specific application	-	
Emission	Infrared reflex	
[Sn] nominal sensing distance	14 m reflex need reflector XUZC50	
Complementary Enclosure material	PBT	
	· · · · · · · · · · · · · · · · · · ·	
Lens material	PMMA	
Maximum sensing distance	20 m reflex	
Output type	Solid state	
Status LED	1 LED (green) for supply 1 LED (yellow) for output state	
[Us] rated supply voltage	1224 V DC	
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)	
Switching frequency	<= 250 Hz	
Voltage drop	<= 1.5 V (closed state)	
voltage drop		
	<= 35 mA (no-load)	
Current consumption Delay first up	<= 35 mA (no-load) < 15 ms	

Delay recovery	< 2 ms
Setting-up	Sensitivity adjustment
Depth	77 mm
Height	92 mm
Width	31 mm
Product weight	0.2 kg
Environment	
Product certifications	CE CSA UL
Ambient air temperature for operation	-2555 °C
Ambient air temperature for storage	-4070 °C
Vibration resistance	7 gn, amplitude = +/- 1.5 mm (f = 1055 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 11 ms) conforming to IEC 60068-2-27
IP degree of protection	IP65 double insulation conforming to IEC 60529 IP67 double insulation conforming to IEC 60529
Offer Sustainability	
RoHS (date code: YYWW)	Compliant - since 1136 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

18 months

Contractual warranty

Warranty period