Thermal Insulator Pad





Description

The product is a medium thermal performance insulator pad consisting of a ceramic filled high temperature silicone rubber coated on electrical grade fiberglass.

The product is designed for applications that require additional thickness to prevent electrical shorts from stamped aluminium heatsinks used in switching mode power supplies (SMPS) and debris from aluminium castings used in automotive motor controls.

Used in applications that require an interface of 2.5°C/watt or higher on a TO-220 mounted at 50 psi pressure.

Specifications

| Thickness | 0.009 inches (0.23mm) |
|--|--------------------------|
| Hardness | 85 Shore A |
| Test Method - Hardness | ASTM D2240 |
| Tensile Strength | 1.3k psi / 9.0 MPa |
| Test Method - Tensile Strength | ASTM D412 |
| Elongation at 45° to Warp/Fill | 0.2% |
| Elongation along Width or Length | 5% |
| Test Method - Elongation | ASTM D412 |
| Mechanical RTI Temperature Rating | 150°C (302°F) |
| Test Method - Mechanical RTI Temperature Rating | UL 746D |
| Colour | Dark Pink |
| UL Flammability Rating | UL 94 V0 |
| Dielectric with Stand Voltage | 4,500V AC |
| Test Method - Dielectric with Stand Voltage | ASTM D149 |
| Dielectric Breakdown Voltage | >6,000V AC |
| Test Method - Dielectric Breakdown Voltage | ASTM D149 |
| Thermal Conductivity | 1.6 w/mk |
| Volume Resistivity | >10 ohm-cm |
| Test Method - Volume Resistivity | ASTM D257 |
| Dielectric Constant at 1MHz | 3.3 |
| Test Method - Dielectric Constant | ASTM D257 |
| Electrical RTI Temperature Rating | 150°C (302°F) |
| Test Method - Electrical RTI Temperature Rating | UL 746D |
| Roll Size | 18" x 164' (457mm × 50m) |
| Pressure Sensitive Adhesive | Single side adhesive |

Thermal resistance of 0.45°C-in2/watt at 50 psi Thermal resistance of 0.35°C-in2/watt at 400 psi

Part Number Table

| Description | Part Number |
|-----------------------|-------------|
| Thermal Insulator Kit | MK3306/TG |

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands Farnell.com/exclusive-brands Element14.com/exclusive-brands



Page <1> 14/06/19 V1.0