Product data sheet Characteristics

XE3SP2151

limit switch contact block - 1NC+2NO - snap action





Range of product	OsiSense XC	
Series name	Standard format	
Product or component type	Limit switch contact block	
Device short name	XE3S	
Associated body	ZCD31 ZCKJD31 ZCKLD31 ZCKMD31 ZCKMD31 ZCF31 ZCF31	7. 2. 2. 2. 3. 4. 4. 4. 4. 4. 4. 4. 4. 4. 4. 4. 4. 4.
Number of poles	3	
Contacts type and composition	2 NO + 1 NC	
Contact operation	Snap action	

Complementary

Complementary				
Product compatibility	XCKD			
	XCKJ			
	XCKL			
	XCKM			
	XCKP			
	XCKS			
Electrical connection	Screw-clamp terminals, clamping capacity: 1 x 0.342 x 0.75 mm²			
Contacts insulation form	Zb			
Contacts material	Silver plated contacts			
Positive opening	With			
Minimum actuation speed	0.01 mm/s			
Contact code designation	B300, AC-15 (Ue = 240 V, Ie = 1.5 A), Ithe = 6 A conforming to EN/IEC 60947-5-1 appendix A			
	R300, DC-13 (Ue = 250 V, Ie = 0.1 A) conforming to EN/IEC 60947-5-1 appendix A			
Resistance across terminals	< 25 mOhm conforming to IEC 60255-7 category 3			
[Ui] rated insulation voltage	300 V conforming to CSA C22.2 No 14			
	400 V degree of pollution 3 conforming to IEC 60947-1			

	300 V conforming to UL 508	
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60664 4 kV conforming to IEC 60947-1	
Short-circuit protection	6 A by gG cartridge fuse	
Electrical durability	5000000 cycles, DC-13 120 V, 1 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C	
	5000000 cycles, DC-13 24 V, 3 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C	
	5000000 cycles, DC-13 48 V, 2 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C	

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0843 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Warranty period	18 months		