## Product data sheet Characteristics

# XY2CZ0130

orange pilot light XY2C - incandescent - clear screw base - 130 V





#### Main

Range of product	Preventa XY2
Component name	XY2C

## Complementary

<del>-</del>	
Screw base	
Incandescent	
Orange	
XY2CH	
130 V AC/DC	
0.035 kg	
	Incandescent Orange XY2CH 130 V AC/DC

#### Environment

Ambient air temperature for storage	-4070 °C
Ambient air temperature for operation	-2570 °C

## Offer Sustainability

Main		
Range of product	Preventa XY2	
Component name	XY2C	
Complementary		
Product or component type	Pilot light	
Bulb base	Screw base	
Bulb type	Incandescent	
Cap/Operator or lens colour	Orange	
Product compatibility	XY2CH	
[] [a] asted sometrous !!	130 V AC/DC	
USJ rated supply voltage	130 V AC/DC	
[Us] rated supply voltage Product weight	0.035 kg	
Product weight  Environment	0.035 kg	
Product weight  Environment  Ambient air temperature for storage	0.035 kg -4070 °C	
Product weight  Environment	0.035 kg	
Product weight  Environment  Ambient air temperature for storage  Ambient air temperature for operation	0.035 kg -4070 °C	
Product weight  Environment Ambient air temperature for storage Ambient air temperature for operation  Offer Sustainability	0.035 kg  -4070 °C  -2570 °C	
Product weight  Environment Ambient air temperature for storage Ambient air temperature for operation  Offer Sustainability Sustainable offer status	0.035 kg  -4070 °C  -2570 °C  Green Premium product	
Product weight  Environment Ambient air temperature for storage Ambient air temperature for operation  Offer Sustainability Sustainable offer status	-4070 °C -2570 °C  Green Premium product  Compliant - since 0842 - Schneider Electric declaration of conformity	
Product weight  Environment Ambient air temperature for storage Ambient air temperature for operation  Offer Sustainability Sustainable offer status  RoHS (date code: YYWW)	0.035 kg  -4070 °C  -2570 °C  Green Premium product	
Product weight  Environment Ambient air temperature for storage Ambient air temperature for operation  Offer Sustainability Sustainable offer status  RoHS (date code: YYWW)	0.035 kg  -4070 °C  -2570 °C  Green Premium product  Compliant - since 0842 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity	
Product weight  Environment  Ambient air temperature for storage  Ambient air temperature for operation  Offer Sustainability  Sustainable offer status  RoHS (date code: YYWW)	0.035 kg  -4070 °C  -2570 °C  Green Premium product  Compliant - since 0842 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity  Reference not containing SVHC above the threshold	
Product weight  Environment  Ambient air temperature for storage	0.035 kg  -4070 °C  -2570 °C  Green Premium product  Compliant - since 0842 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity  Reference not containing SVHC above the threshold  Reference not containing SVHC above the threshold	

Warranty period

18 months