Product datasheet Characteristics

ABE7CPA410

connection sub-base ABE7 - for distribution of 4 analog channels protected



Advantys Telefast ABE7
Connection sub-base for analogue channels
4
Screw type terminals, clamping capacity: 1 x 0.091 x 1.5 mm² AWG 28AWG 16 flexible with cable end Screw type terminals, clamping capacity: 1 x 0.141 x 2.5 mm² AWG 26AWG 12 solid Screw type terminals, clamping capacity: 1 x 0.141 x 2.5 mm² AWG 26AWG 14 flexible without cable end
Screw type terminals, clamping capacity: 2 x 0.092 x 0.75 mm ² AWG 28AWG 20 flexible with cable end Screw type terminals, clamping capacity: 2 x 0.22 x 2.5 mm ² AWG 24AWG 14 solid

Complementary

o o mpio montary	
Function of module	Distribution of supply and 4 analogue channels protected isolated , compatible with Modicon M340
Product compatibility	BMXAMI0410 compatible with Modicon M340
Connection to PLC	SUB-D 25
Fixing mode	By clips on 35 mm symmetrical DIN rail By screws on solid plate with fixing kit
[Ui] rated insulation voltage	2000 V between terminals/mounting rails
Installation category	II conforming to IEC 60664-1
Tightening torque	0.6 N.m (with flat Ø 3.5 mm)
Product weight	0.18 kg

Environment

Environment		v.
Product certifications	BV	ი ი
	CSA	Ped
	UL	intended
	DNV	ot ii
	GL	υ Σ
	LROS (Lloyds register of shipping)	i. ion
IP degree of protection	IP20 conforming to IEC 60529	entat
Resistance to incandescent wire	750 °C, extinction time: < 30 s conforming to IEC 60695-2-11	OCUT
Shock resistance	15 gn for 11 ms conforming to IEC 60068-2-27	his d
Vibration resistance	2 gn (f = 10150 Hz) conforming to IEC 60068-2-6	
Resistance to electrostatic discharge	4 kV (contact) conforming to IEC 61000-4-2 level 3	oisclain————————————————————————————————————

8 kV (air) conforming to IEC 61000-4-2 level 3

Resistance to radiated fields	10 V/m (260000001000000000 Hz) conforming to IEC 61000-4-3 level 3
Resistance to fast transients	2 kV conforming to IEC 61000-4-4 level 3
Ambient air temperature for operation	060 °C conforming to IEC 61131-2
Ambient air temperature for storage	-4080 °C conforming to IEC 61131-2
Pollution degree	2 conforming to IEC 60664-1

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1017 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity

Contractual warranty

Warranty period	18 months