

True RMS Mini Clamp Meter



Features

- 2000 Counts Display
- LCD Backlight
- Manual & Auto Ranging
- 17mm Jaw Capacity
- Diode and Continuity Test
- NCV Detector
- VFC Function
- Continuity Buzzer
- Data Hold
- Zero/MAX/MIN Modes
- Auto Power Off
- Low Battery Indication
- Input Protection
- Input Impedance for DCV: 10M Ω

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk



True RMS Mini Clamp Meter



General Characteristics

Safety Rating	: CAT II 600V, CAT III 300V
Power	: AAA 1.5V Batteries × 2
LCD Size	: 39.3mm × 26.5mm
Colour	: Orange and Grey
Weight	: 170g
Dimension	: 175mm × 60mm × 33.5mm
Standard Accessories	: Batteries, Test Lead & User Manual

Electrical Specifications

Parameters	Range	Best Accuracy
AC Current	2A/20A/100A	±(2.5% +5 digits)
DC Current	2A/20A/100A	±(2% +3 digits)
AC Voltage	2V/20V/200V/600V	±(1% +3 digits)
DC Voltage	200mV/2V/20V/200V/600V	±(0.7% +3 digits)
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	±(1% +2 digits)
Capacitance	2nF/20nF/200nF/2μF/20μF/200μF/2mF/20mF	±(4% +5 digits)
Jaw Capacity	17mm	
Auto Power Off	Around 15 minutes	
Low Battery Indication	≤ 2.5V	

Part Number Table

Description	Part Number
True RMS Mini Clamp Meter, 17mm Jaw	72-2985

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell Limited 2016.



Weatherproof Tool Case with Foam



Features

- Built-in O-ring with secure latches prevent water and moisture damage to contents
- Padlock compatible for additional security
- Built-in pressure relief valve
- High-density polymer provides outstanding strength and corrosion resistance
- 2-3/4" Layer of cubed foam, 1/2" Base layer foam & 1" Top lid egg-crate foam

Specifications

Case Material	: Polymer
Case Colour	: Yellow
External Dimensions - Metric (W × D × H)	: 342.9mm × 292.1mm × 152.4mm
External Dimensions - Imperial (W × D × H)	: 13.5" × 11.5" × 6"
Internal Dimensions - Metric (W × D × H)	: 304.8mm × 228.6mm × 127mm
Internal Dimensions - Imperial (W × D × H)	: 12" × 9" × 5"
No. of Latches	: 2

Part Number Table

Description	Part Number
Weatherproof Tool Case w/ Foam, Polymer, Yellow	22-24146

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. DURATOOL is the registered trademark of the Group. © Premier Farnell Limited 2016.

