

Wall bracket - UCS WM-B 7035 - 2203718

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Adapter for mounting the UCS housing on the wall, material: polyamide, color: light gray similar to RAL 7035, used instead of UCS CC corner insert; only used in conjunction with UCS GD 9005 adhesive pad

Your advantages

- ☑ Practical customization options
- ▼ Tool-free snap-in principle enables easy mounting on the device panel
- Flexible mounting options for the control cabinet and use in the field
- ☑ Can be adapted to suit the application, thanks to identical receptacles in the housing
- Different colors for high recognition value inside and outside the control cabinet



Key Commercial Data

Packing unit	1 pc
GTIN	4 0 5 5 6 2 6 4 3 6 5 9 3
GTIN	4055626436593
Weight per Piece (excluding packing)	14.300 g
Sales Key	ACFCAZ

Technical data

Item properties

Туре	UCS WM-B 7035
Order No.	2203718
Housing type	Universal housings

Measurements

Width [w]	16 mm
Height [h]	25.95 mm
Depth [d]	21 mm
Diameter mounting hole	4 mm

Material specifications



Wall bracket - UCS WM-B 7035 - 2203718

Technical data

Material specifications

Color (RAL)	light gray (7035)
Insulating material	PA
Flammability rating according to UL 94	V0
Housing material	PA

Ambient conditions

Ambient temperature (storage/transport)	-40 °C 70 °C
Ambient temperature (assembly)	-5 °C 100 °C
Ambient temperature (operation)	-40 °C 100 °C (depending on power dissipation)

Packaging information

Pieces per package	1
Denomination packing units	Pcs.

Standards and regulations

Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 5.1	27180506
eCl@ss 6.0	27180800
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 5.0	EC001031
ETIM 6.0	EC001031
ETIM 7.0	EC001031

Phoenix Contact 2019 @ - all rights reserved http://www.phoenixcontact.com