

Wall bracket - UCS WM-B 9005 - 2203719

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


Adapter for mounting the UCS housing on the wall, material: polyamide, color: black similar to RAL 9005, used instead of UCS CC corner insert; only used in conjunction with UCS GD 9005 adhesive pad



Your advantages

- Practical customization options
- Tool-free snap-in principle enables easy mounting on the device panel
- Flexible mounting options for the control cabinet and use in the field
- Can be adapted to suit the application, thanks to identical receptacles in the housing
- Different colors for high recognition value inside and outside the control cabinet

Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 440002
GTIN	4055626440002
Weight per Piece (excluding packing)	14.300 g
Sales Key	ACFCAZ

Technical data

Item properties

Type	UCS WM-B 9005
Order No.	2203719
Housing type	Universal housings

Measurements

Width [w]	16 mm
Height [h]	25.95 mm
Depth [d]	21 mm
Diameter mounting hole	4 mm

Material specifications

Wall bracket - UCS WM-B 9005 - 2203719

Technical data

Material specifications

Color (RAL)	black (9005)
Insulating material	PA
Flammability rating according to UL 94	V0
Housing material	PA

Ambient conditions

Ambient temperature (storage/transport)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Ambient temperature (operation)	-40 °C ... 100 °C (depending on power dissipation)

Packaging information

Pieces per package	1
Denomination packing units	Pcs.

Standards and regulations

Flammability rating according to UL 94	V0
--	----

Classifications

eCl@ss

eCl@ss 5.1	27180506
eCl@ss 6.0	27180800
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 5.0	EC001031
ETIM 6.0	EC001031
ETIM 7.0	EC001031