

5.2mm × 20mm Axial Leaded Fast-Acting Ceramic Cartridge Fuse

multicomp PRO

**RoHS
Compliant**



Specification


Current Rating	: 10A to 25A
Voltage Rating	: 420V AC / DC
Fuse Body Material	: Ceramic
Termination Material	: Nickel Plated Brass Caps
Operating Temperature	: -55°C to +125°C
Interrupting Current Rating	: 10A and 16A : 300A at 420V AC/DC 400A at 450V DC 200A at 500V AC 200A at 600V AC
	25A : 300A at 420V DC 400A at 450V DC 200A at 420V AC 200A at 500V AC

Electrical Characteristics

Rating	100% Rating	210% Rating	275% Rating		400% Rating		1000% Rating	
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
10A to 25A	60min	30min	40ms	20Sec.	10ms	1Sec.	-	30ms

Part Number	Ampere Rating (A)	Voltage Rating (V)	Nominal Cold Resistance (Ohms)	Nominal Melting I ² t (A ² sec.)
MP000847	10	420	0.01033	128
MP000848	16		0.00615	260
MP000849	25		0.00246	1250

Mechanical Dimensions



Dimensions : Millimetres

Part Number Table

Description	Part Number
Cartridge Fuse, Fast-Acting, Ø5.2mm × 20mm, 10A, 420V	MP000847
Cartridge Fuse, Fast-Acting, Ø5.2mm × 20mm, 16A, 420V	MP000848
Cartridge Fuse, Fast-Acting, Ø5.2mm × 20mm, 25A, 420V	MP000849

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands
Farnell.com/exclusive-brands
Element14.com/exclusive-brands

multicomp PRO