


**RoHS
Compliant**



Features

- Electrical life: 100,000 cycles
- 3.2mm × 4mm miniature tact switch
- Vertical Push Type
- Halogen Free




Applications

- Control panel
- Remote controls
- Keyless entry devices


Specifications

Contact Rating	: 10μA, 1V DC to 50mA, 16V DC
Contact Resistance	: 500mΩ max.
Insulation Resistance	: 100MΩ min. 100V DC
Dielectric strength	: 250V AC/1 minute
Operating Force	: 160±50gf / 260±80gf / 400±100gf
Travel	: 0.12mm
Operating Life	: 100,000 cycles
Operating Temperature	: -30°C to +85°C
Storage Temperature	: -30°C to +85°C

Diagram




P.C.B. LAYOUT



Dimensions : Millimetres

Circuit



Part Number Table

Description	Part Number
Tact Switch, 16V DC, SPST, 160gf, SMD	MP000722
Tact Switch, 16V DC, SPST, 260gf, SMD	MP000723
Tact Switch, 16V DC, SPST, 400gf, SMD	MP000724

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands
Farnell.com/exclusive-brands
Element14.com/exclusive-brands