



8132 Paired - Low Capacitance Computer Cable for EIA RS-232/485

 	<p>For more information please call <b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p> <p><b>Related Documents : No. 5 for Paired Cables (Western Electric Standard).pdf</b></p>
--	---

**Description:**

28 AWG stranded (7x36) TC conductors, Datalene® insulation, overall Beldfoil® (100% coverage) + TC braid shield (65% coverage), 28 AWG stranded TC drain wire, PVC jacket.

**PHYSICAL CHARACTERISTICS:**

**CONDUCTOR:**

Number of Pairs	2
Total Number of Conductors	4
AWG	28
Stranding	7x36
Conductor Material	TC - Tinned Copper

**INSULATION:**

Insulation Material Trade Name	Datalene®
Insulation Material	FPE - Foam Polyethylene
Lay Length	.75 in.
Twists/ft.	15.6

Pair Color Code Chart :

Number	Color	Number	Color
1	White/Blue & Blue/White	2	White/Orange & Orange/White

**OUTER SHIELD:**

Outer Shield Material Trade Name	Beldfoil®
Outer Shield Type	Tape/Braid

Outer Shield Material :

Layer Number	Material Trade Name	Type	Material	% Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape w/Shorting Fold	100
2		Braid	TC - Tinned Copper	65

Outer Shield % Coverage	100 %
-------------------------	-------



**8132 Paired - Low Capacitance Computer Cable for EIA RS-232/485**

**OUTER SHIELD DRAIN WIRE :**

Outer Shield Drain Wire AWG	28
Outer Shield Drain Wire Stranding	7x36
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

**OUTER JACKET:**

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

**OVERALL NOMINAL DIAMETER:**

Overall Nominal Diameter	.220 in.
--------------------------	----------

**MECHANICAL CHARACTERISTICS:**

Operating Temperature Range	-30°C To +80°C
UL Temperature Rating	80°C (UL AWM Style 2919)
Bulk Cable Weight	30 lbs/1000 ft.
Min. Bend Radius (Install)	2.5 in.

**APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:**

**APPLICABLE STANDARDS:**

NEC/(UL) Specification	CL2
AWM Specification	UL Style 2919 (30 V 80°C)
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004

**FLAME TEST:**

UL Flame Test	UL1685 UL Loading
---------------	-------------------

**PLENUM/NON-PLENUM:**

Plenum (Y/N)	N
--------------	---

**ELECTRICAL CHARACTERISTICS:**

Nom. Characteristic Impedance	120 Ohms
Nom. Capacitance Conductor to Conductor @ 1 KHz	11 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	20 pF/ft
Nominal Velocity of Propagation	78 %
Nom. Conductor DC Resistance @ 20 Deg. C	65 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20 Deg. C	5.1 Ohms/1000 ft
Max. Operating Voltage - UL	30 V RMS (UL AWM Style 2919); 150 V RMS
Max. Recommended Current	1 Amp per conductor @ 25°C

**NOTES:**

