

R73, Film, Film/Foil Polypropylene, Automotive Grade, 220 pF, 5%, 2000 VDC, 85°C, Lead Spacing = 15mm



| General Information | |
|---------------------|---|
| Series: | R73 |
| Dielectric: | Film/Foil Polypropylene |
| Style: | Radial |
| Features: | Automotive Grade, Pulse |
| RoHS: | Yes |
| Lead: | Wire Leads |
| Qualifications: | AEC-Q200 |
| AEC-Q200: | Yes |
| Miscellaneous: | Above 85C DC And AC Voltage Derating Is 1.25%/C |

| Dimensions | |
|------------|-----------------|
| L | 18mm +0.3mm |
| H | 11mm +0.1mm |
| T | 5mm +0.2mm |
| S | 15mm +/-0.4mm |
| LL | 30mm +5mm |
| F | 0.8mm +/-0.05mm |

| Specifications | |
|------------------------|---------------------------------------|
| Capacitance: | 220 pF |
| Capacitance Tolerance: | 5% |
| Voltage AC: | 500 VAC |
| Voltage DC: | 2000 VDC |
| Temperature Range: | -55/+105C |
| Rated Temperature: | 85°C |
| Dissipation Factor: | 0.03% 1kHz, 0.04% 10kHz, 0.10% 100kHz |
| Insulation Resistance: | 100 GOhms |
| Max dV/dt: | 54000 V/us |
| Inductance: | 10 nH |

| Packaging Specifications | |
|--------------------------|-----------|
| Packaging: | Bulk, Bag |
| Packaging Quantity: | 1000 |