



Features

- Low cost
- Diffused junction
- Ultra fast switching for high efficiency
- Low reverse leakage current
- Low forward voltage drop
- High current capability
- The plastic material carries UL recognition 94V-0

Mechanical Data

Case	: JEDEC DO-41 molded plastic
Polarity	: Colour band denotes cathode
Weight	: 0.012 ounces, 0.34 grams
Mounting Position	: Any
Reverse Voltage	: 50 to 1000 Volts
Forward Current	: 1 Ampere

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Characteristics	Symbol	UF4001+	UF4002+	UF4003+	UF4005+	UF4007+	Unit
Max. Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	800	V
Max. RMS Voltage	V_{RMS}	35	70	140	280	560	V
Max. DC Blocking Voltage	V_{DC}	50	100	200	400	800	V
Max. Average Forward Rectified Current @ $T_A = 75^\circ C$	$I_{(AV)}$	1.0					A
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Super Imposed on Rated Load (JEDEC Method)	I_{FSM}	30					A
Peak Forward Voltage at 1A DC	V_F	1		1.3	1.7	V	
Maximum DC Reverse Current @ $T_J = 25^\circ C$ at Rated DC Blocking Voltage @ $T_J = 100^\circ C$	I_R	5 100					μA
Maximum Reverse Recovery Time (Note 1)	T_{RR}	50			75	nS	
Typical Junction Capacitance (Note 2)	C_J	20			10	pF	
Typical Thermal Resistance (Note 3)	$R_{\theta JA}$	25					$^\circ C/W$
Operating Temperature Range	T_J	-55 to +150					$^\circ C$
Storage Temperature Range	T_{STG}						

- Notes :**
1. Measured with $I_F = 0.5A$, $I_R = 1A$, $I_{RR} = 0.25A$
 2. Measured at 1MHz and applied reverse voltage of 4V DC
 3. Thermal resistance junction to ambient.
 4. The typical data above is for reference only

Rating and Characteristic Curves

FIG. 1 – FORWARD CURRENT DERATING CURVE




FIG. 2 – MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG. 3 – TYPICAL JUNCTION CAPACITANCE






FIG.4-TYPICAL FORWARD CHARACTERISTICS



Dimensions:

DO-41



Dimensions : Inches (Millimetres)

Part Number Table

Description	Part Number
High Efficiency Rectifiers (Ultra Fast)	UF4001+
	UF4002+
	UF4003+
	UF4005+
	UF4007+

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.