5 Ports Gigabit Compact Ethernet Switch



RoHS Compliant

Features

- · 5 Gigabit Ethernet ports
- · No software required simply plug in and connect
- · Industrial temperature range works in extreme conditions
- · Redundant dual power inputs reduces risk of power outage
- · Compact design efficient use of DIN rail
- · Integral DIN mount

Specifications

Ethernet Ports : 5 × RJ45 jack, 1 Gigabit autosensing, crossover auto sensing (Auto MDIX)

Operating Temperature : -40°C to +80°C / -40°F to +176°F

Power Consumption : 3.6W Max: 720mA @ +5V DC / 120mA @ +30V DC

Power Supply Input : Unregulated +5 Volts to +30 Volts DC, reverse polarity protection

Redundant Dual Power Inputs : +5V DC to +30V DC


Unmanaged Gigabit Ethernet


Housing : IP-20 rated non-conducting polyamide case with Easy Wire Removable screw terminal block

Weight : 0.115 kg

Dimensions : 99mm × 94mm × 23mm

Diagram





Dimensions: Millimetres

Part Number Table

Description	Part Number
Compact Ethernet Switch, 5 Ports, DIN Rail Mount	MP-515

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

