




Home > Products > MICRO SWITCH™ Toggle Switches > TL > Product Page

### Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

## 1TL887-6F



Actual product appearance may vary.

**TL Series Toggle Switch, 1 pole, 2 position, Screw terminal, Locking Lever**

### Features

Environmentproof sealing  
 1,2, and 4 pole circuitry  
 Standard and pull-to-unlock levers  
 2 and 3 position, maintained and momentary toggle action  
 Temperature range: -85° F to +160° F  
 Completely sealed switching chamber  
 Step-design case provides added space between terminals to help prevent shorting  
 UL recognized, CSA certified  
 CE approved

### Potential Applications

Industrial machinery and equipment  
 Military and commercial aviation  
 Construction equipment  
 Test instruments  
 Agricultural machinery  
 Process control  
 Medical instrumentation

### Description








MICRO SWITCH™ TL Series toggle switches have high strength, temperature resistant, non-tracking case material and silver cadmium oxide contacts. Pull-to-unlock toggle levers prevent accidental operation; the lever must be pulled approx. 2,3 mm (0.09 inches) to change positions.

### Supporting Documentation

[Accessory: Seals](#)

[Accessory: Nuts](#)

[Engineering Drawing](#)

Product Specifications					
Circuitry/Operating action	<table border="0"> <tr> <td style="text-align: center;"><b>Keyway Momentary Position</b></td> <td style="text-align: center;"><b>Opposite Keyway Position</b></td> </tr> <tr> <td style="text-align: center;"></td> <td style="text-align: center;"></td> </tr> </table>	<b>Keyway Momentary Position</b>	<b>Opposite Keyway Position</b>		
<b>Keyway Momentary Position</b>	<b>Opposite Keyway Position</b>				
					
Product Type	MICRO SWITCH™ Toggle Switch				
Lever Lock	 Locked in extreme position (Opposite keyway)				
Ampere/Voltage Range (Resistive Load)	0.5 A to 15 A at 0.5 Vdc to 28 Vdc, 0.5 A to 10 A at 0.5 Vac to 7 Vac, 0.75 A at 115 Vdc, 0.5 A at 250 Vdc				
Circuitry	SPST				
Action	2 position				
Mounting	Bushing 15/32 in				
Termination	Screw				
Lever Type	Locking				
UL/CSA Rating Code	L192: 10 A - 125, 250, 277 Vac; 1/4 Hp - 125 Vac; 1/2 Hp - 250, 277 Vac; 3 A - 125 Vac "L"				
Comment	Gold Plated Contacts				
Availability	Global				
UNSPSC Code	30211908				
UNSPSC Commodity	30211908 Toggle switches				
Series Name	TL				

### Keyword Search

Search for product and support information.

All Sensing and Control

### Product Search

Part number search:

Use (\*) to expand search

Specification Search