Note: This datasheet may be out of date.
Please download the latest datasheet of PTGL10ARR27M1B51B0 from the official website of Murata
Manufacturing Co., Ltd.

https://www.murata.com/en-eu/products/productdetail?partno=PTGL10ARR27M1B51B0

## PTGL10ARR27M1B51B0













# Appearance & Shape











- 1. Best suited to meet the requirements for power supplies and motor protection. Error-free operation is assured by rush current.
- 2. Circuit is protected until current is turned off.
- 3. Restores the original low resistance value automatically once the overload is removed.
- 4. Non-contact design leads to long life and no noise.

  Durable and strong against mechanical vibration and shock because it is a solid element.



Limited Usage

Consumer Grade



## Packaging Information

Packaging	Specifications	Minimum Order Quantity
В0	Bulk(Bag)	300

1 of 3

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



F: Lead Space

d: Lead Diameter

Shape

Mass

### Manufacturing Co., Ltd. https://www.murata.com/en-eu/products/productdetail?partno=PTGL10ARR27M1B51B0

5mm

0.6mm

Lead

0.38g

# PTGL10ARR27M1B51B0



Max. Voltage	16V
Hold Current	800mA
Measure Condition of Hold Current	(at +60°C)
Hold Current (2)	1025mA
Measure Condition of Hold Current (2)	(at +25°C)
Trip Current	1900mA
Measure Condition of Trip Current	(at +25°C)
Trip Current(2)	2250mA
Measure Condition of Trip Current(2)	(at -10°C)
Max. Current	8A
Resistance (25°C)	0.27Ω
Resistance Value Tolerance (at 25°C)	±20%
Power Consumption(typ)	1.8W
Operating Temperature Range	-10°C to 60°C
D: Outer Dimension	10.1mm
Thickness	3.5mm
H: Height	15mm

2 of 3

### Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering




<sup>1.</sup> This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


Note: This datasheet may be out of date.  $\underline{ \text{Please download the latest datasheet of PTGL10ARR27M1B51B0 from the official website of Murata} \\$ Manufacturing Co., Ltd.

https://www.murata.com/en-eu/products/productdetail?partno=PTGL10ARR27M1B51B0

# PTGL10ARR27M1B51B0








Resistance-Temperature Charac.

Protective Threshold Current Range



Operating Time (Typical Curve)

3 of 3

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/11/25