

Surge protection plug - TC EXTENDER PT-IQ-1S - 2702257


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Replaceable surge protection module, only for Ethernet extender TC EXTENDER 4001 ETH-1S (2702253), 1 SHDSL port, two-wire protection for floating SHDSL cables, two-level protective circuit



Key Commercial Data

Packing unit	1 pc
GTIN	 4 0 5 5 6 2 6 0 5 7 7 2 9
GTIN	4055626057729
Weight per Piece (excluding packing)	48.680 g
Custom tariff number	85363090
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

Dimensions

Width	22 mm
Height	96 mm
Depth	80 mm

Ambient conditions

Degree of protection	IP20
----------------------	------

General

Net weight	48.68 g
------------	---------

Standards and Regulations

Standards/regulations	IEC 61643-21
	IEC 60664-1
IEC test classification	B1
	C1

Surge protection plug - TC EXTENDER PT-IQ-1S - 2702257

Technical data

Standards and Regulations


	C2
	C3
	D1
Noxious gas test	ISA-S71.04-1985 G3 Harsh Group A

Environmental Product Compliance


China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Schematic diagram



Schematic diagram



Replacement of protective module

Classifications

eCl@ss

eCl@ss 5.1	27242200
eCl@ss 6.0	27130800
eCl@ss 7.0	27130807
eCl@ss 8.0	27130807
eCl@ss 9.0	27130807

ETIM

ETIM 2.0	EC000943
ETIM 3.0	EC000943
ETIM 4.0	EC000943
ETIM 5.0	EC000943
ETIM 6.0	EC000943

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610

Surge protection plug - TC EXTENDER PT-IQ-1S - 2702257

Classifications

UNSPSC

UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Accessories

Necessary add-on products

Modem - TC EXTENDER 4001 ETH-1S - 2702253



Managed Ethernet extender, point-to-point connections, data rates up to 15.3 Mbps, distances of up to 20 km on in-house copper cables, replaceable surge protection, 1 SHDSL port, 1 LAN port, diagnostics via Ethernet