

Philips screwdriver - SF-PZ 3-150 - 1212565

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Screwdriver, PZ crosshead (lasered), uninsulated, size: PZ 3 x 150, 2-component grip, with non-slip grip

Your advantages

- Screwdrivers for Phillips screws with Pozidriv and Phillips Recess screw head

Key Commercial Data

Packing unit	10 pc
GTIN	 4 046356 590006
GTIN	4046356590006
Weight per Piece (excluding packing)	156.300 g
Custom tariff number	82054000
Country of origin	Czech Republic
Note	Made to Order (non-returnable)

Technical data

Dimensions

Length (b)	262 mm
Width (a)	40 mm
Blade width	8 mm
Blade height	150 mm
Wrench size	0 mm

General

Type	Phillips
	straight
Material	alloyed tool steel
Test standard	DIN ISO 8764-1

Standards and Regulations

Test standard	DIN ISO 8764-1
---------------	----------------

Environmental Product Compliance

Philips screwdriver - SF-PZ 3-150 - 1212565

Technical data

Environmental Product Compliance

California Proposition 65	Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration
---------------------------	---

Drawings

Pictogram



Classifications

eCl@ss

eCl@ss 10.0.1	21040406
eCl@ss 4.0	21040400
eCl@ss 4.1	21040400

Philips screwdriver - SF-PZ 3-150 - 1212565

Classifications

eCl@ss

eCl@ss 5.0	21040400
eCl@ss 5.1	21040400
eCl@ss 6.0	21040400
eCl@ss 7.0	21040406
eCl@ss 8.0	21040406
eCl@ss 9.0	21040406

ETIM

ETIM 4.0	EC000144
ETIM 5.0	EC000144
ETIM 6.0	EC000144
ETIM 7.0	EC000144

UNSPSC

UNSPSC 6.01	27111701
UNSPSC 7.0901	27111701
UNSPSC 11	27111701
UNSPSC 12.01	27111701
UNSPSC 13.2	27111701
UNSPSC 18.0	27111701
UNSPSC 19.0	27111701
UNSPSC 20.0	27111701
UNSPSC 21.0	27111701

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		RU C- DE.AI30.B.01750
-----	--	--------------------------
