

Single Channel Linear Bench Top DC Power Supplies

multicomp PRO



MP710086
MP710086 US



MP710087
MP710087 US

Application

Military R&D, Quality Inspection, Circuit Functional Testing, Automotive Circuit Testing, Education and Technical Training
Electronic component testing and aging analysis, Monitoring battery charging curve.

Specifications

Characteristic	Part Number	
	MP710086 & MP710086 US	MP710087 & MP710087 US
Channel	Single Channel Output	
Total Output Power	150W	180W
Channel Output	0 - 30V / 0 - 5A × 1-CH	0 - 60V / 0 - 3A × 1-CH
Display	3.7 inch colour LCD display	
Dimension	117mm(L) × 194mm(H) × 295mm(D)	
Weight	Approx. 5.6 kg	Approx. 5.8 kg
Interface	RS232 and USB	

Characteristic		MP710086 & MP710086 US	MP710087 & MP710087 US
Rated Output (0°C to -40°C)	Voltage	0 to 30V	0 to 60V
	Current	5A	3A
Load Regulation	Voltage	≤0.01% +3mV	
	Current	≤0.01% +3mA	
Power Regulation	Voltage	≤0.01% +3mV	
	Current	≤0.01% +3mA	
Setting Resolution	Voltage	1mV	
	Current	1mA	

Newark.com/exclusive-brands
Farnell.com/exclusive-brands
Element14.com/exclusive-brands

multicomp PRO

Single Channel Linear Bench Top DC Power Supplies



Characteristic		MP710086 & MP710086 US	MP710087 & MP710087 US
Read Back Resolution	Voltage	1mV	
	Current	1mA	
Set Point Accuracy (within 12 months) (25°C ±5°C)	Voltage	≤0.03% +10mV	
	Current	≤0.1% +5mA	
Read Back Resolution (25°C ±5°C)	Voltage	≤0.03% +10mV	
	Current	≤0.1% +5mA	
Ripple/Noise (20Hz - 20MHz)	Voltage (Vp-p)	≤4mVp-p	
	Voltage (rms)	≤1mVrms	
	Current (rms)	≤4mA _{rms}	
Output Temperature Coefficient (0°C to +40°C)	Voltage	≤0.03% +10mV	
	Current	≤0.1% +5mA	
Read Back Temperature Coefficient	Voltage	≤0.03% +10mV	
	Current	≤0.1% +5mA	
Response Time		100µs	
Storage		5 groups of data	
Working Temperature		0 - 40°C	

Note: The instrument must be operated continuously for more than 30 minutes at the specified temperature to ensure the following parameters.

Accessories Included : (UK / EU) or US Power Cord, Fuse, RS232 Cable, USB Cable and User Manual
 Standard Warranty : 12 Months

Part Number Table

Description	Part Number
Bench Top Power Supply, 150W, 30V DC, 5A, UK/EU	MP710086
Bench Top Power Supply, 180W, 60V DC, 3A, UK/EU	MP710087
Bench Top Power Supply, 150W, 30V DC, 5A, US	MP710086 US
Bench Top Power Supply, 180W, 60V DC, 3A, US	MP710087 US

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands
 Farnell.com/exclusive-brands
 Element14.com/exclusive-brands

