muRata Inductor Data Sheet

LQM2HPN1R0MGC# "#" indicates a package specification code.

In Production General 85 Multi-RoHS REACH

< List of part numbers with package codes > LQM2HPN1R0MGCL , LQM2HPN1R0MGCB

Shape



1008 (2520)

References

Packaging code	Specifications	Minimum quantity
L	φ180mm Embossed taping	3000
В	Packing in bulk	1000

Mas	ss (Тур.)
1 piece	0.022g

Specifications

Size code in inch (mm)

Inductance	1.0μH ±20%
Inductance test frequency	1MHz
Rated current (Itemp) (Based on Temperature rise)	1500mA
Max. of DC resistance	0.100Ω
Avg. of DC resistance	0.08Ω±25%
Self resonance frequency (min.)	50MHz
Operating temperature range	-30 °C to 85 °C
Class of magnetic shield	Ferrite Core
Series	LQM2HPN_GC

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.


2. This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Chart of characteristic data (The charts below may show another part number which shares its characteristics.)


Inductance-Frequency characteristics (Typ.)





Inductance-Current characteristics (Typ.)

Temperature rise characteristics (Typ.)



2 of 2

🔔 Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.