LQG15HS7N5G02# "#" indicates a package specification code.















< List of part numbers with package codes > LQG15HS7N5G02D , LQG15HS7N5G02J , LQG15HS7N5G02B

Shape



References

	Packaging code	Specifications	Minimum quantity	
	D	φ180mm Paper taping	10000	
	J	φ330mm Paper taping	50000	
	В	Packing in bulk	1000	

Mass (Typ.)	
1 piece	0.001g

Specifications

Inductance	7.5nH ±2%		
Inductance test frequency	100MHz		
Rated current (Itemp) (Based on Temperature rise)	550mA		
Max. of DC resistance	0.24Ω		
Q (min.)	8		
Q test frequency	100MHz		
Self resonance frequency (min.)	4200MHz		
Operating temperature range (Self-temperature rise is not included)	-55°C to 125°C		
Series	LQG15HS 02		

1 of 2



^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




^{2.} This datasheet has only typical specifications because there is no space for detailed specifications.

Chart of characteristic data (The charts below may show another part number which shares its characteristics.)

Inductance-Frequency characteristics (Typ.)



Q-Frequency characteristics (Typ.)



2 of 2



1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

