muRata Inductor Data Sheet

LQW2BAS82NG00# "#" indicates a package specification code.



< List of part numbers with package codes >

LQW2BAS82NG00L , LQW2BAS82NG00K , LQW2BAS82NG00B





1.42 ±0.1mm

0805 (2015)

Packaging code	Specifications	Minimum quantity
L	φ180mm Embossed taping	2000
К	φ330mm Embossed taping	8000
В	Packing in bulk	500

Mass (7	Гур.)
1 piece	0.014g

Specifications

Size code in inch (mm)

T size

Inductance	82nH ±2%
Inductance test frequency	150MHz
Rated current (Itemp) (Based on Temperature rise)	400mA
Max. of DC resistance	0.42Ω
Q (min.)	65
Q test frequency	500MHz
Self resonance frequency (min.)	1330MHz
Operating temperature range (Self-temperature rise is not included)	-55°C to 125°C
Series	LQW2BAS_00

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.


2. This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Chart of characteristic data (The charts below may show another part number which shares its characteristics.)

Q-Frequency characteristics (Typ.)





🔔 Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.