muRata Inductor Data Sheet

# LQW2BHN47NG03# "#" indicates a package specification code.



< List of part numbers with package codes > LQW2BHN47NG03L, LQW2BHN47NG03K

#### Shape



### References

Packaging code	Specifications	Minimum quantity
L	$\phi$ 180mm Embossed taping	2000
К	$\phi$ 330mm Embossed taping	7500

	Mass (Typ.)	
1 p	ece	0.009g

### Specifications

Inductance	47nH ±2%
Inductance test frequency	100MHz
Rated current (Itemp) (Based on Temperature rise)	450mA
Max. of DC resistance	0.23Ω
Q (min.)	40
Q test frequency	200MHz
Self resonance frequency (min.)	1600MHz
Operating temperature range (Self-temperature rise is not included)	-40°C to 85°C
Series	LQW2BHN_03

#### 🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






## Chart of characteristic data (The charts below may show another part number which shares its characteristics.)

Q-Frequency characteristics (Typ.)





#### 🔔 Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

2 of 2