

## S334e

Bright projection









- Bright SVGA projector 3800 ANSI lumens
- Easy connectivity HDMI, VGA, USB Power
- Clear, powerful audio 10W speaker
- Lightweight and portable

Project bright vibrant presentations effortlessly any time of day. Designed for meeting rooms and classrooms, the S334e boasts amazing colour, long lamp life and energy-saving features to provide you with a low overall cost of ownership.



## **Specifications**

Weight and dimensions

Dimensions (W x D x H)

Net weight

Display/image         DLP           Resolution         SVGA (800x600)           Brightness         3,800 lumens           Contrast ratio         22,000:1           Native aspect ratio - compatible         4:3           Aspect ratio - compatible         16:9           Keystone correction - vertical         +/-40°           Horizontal scan rate         15:38 − 91.15K/rz           Vertical scan rate         50 − 85(120 for 3D)Hz           Uniformity         75%           Screen size         0.71m − 7.73m (27:78" − 304.4") diagonal           Lamp info         Lamp           Light source type         Lamp           Lamp bife hours (up to)         6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)           Optical         Throw ratio           Throw ratio         1.94:1 − 2.16:1           Projection distance (m)         1m - 12m           Zoom         1.1           Zoom type         Manual           Focal length (mm)         21.85 − 24           Native orfset         115%           Connections         Inputs 1 × HDMI 1.4a, 3D support, 1 × VGA (YPbP/RGB), 1 × Composite video, 1 × Audio 3.5mm           Outputs 1 x Audio 3.5mm, 1 x USB-A power 1A         General           PC compatibility	Specifications	
Bresolution         SVGA (800x600)           Brightness         3,800 lumens           Contrast ratio         22,000-1           Native aspect ratio         4:3           Aspect ratio - compatible         16:9           Keystone correction - vertical         +7-40°           Horizontal scan rate         15:38 ~ 91.15kHz           Vertical scan rate         50 ~ 85(120 for 3D)Hz           Uniformity         75%           Screen size         0.71m ~ 7.73m (27.78" ~ 304.4") diagonal           Lamp life         Lamp           Light source type         Lamp           Lamp wats         203           Lamp life hours (up to)         6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)           Optical         Throw ratio           1.94:1 ~ 2.16:1         Projection distance (m)           2.0m         1.1           2.0m         Manual           Focal length (mm)         21.85 ~ 24           Native offset         115%           Connectivity         Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm, 1 x USB-A power 1A           General         Noise level (typical)         27 ds           PC compatibility         HD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac <t< th=""><th>Display/image</th><th></th></t<>	Display/image	
Brightness	Display technology	DLP
Contrast ratio         22,000:1           Native aspect ratio         4:3           Aspect ratio - compatible         16:9           Keystone correction - vertical         +/-40°           Horizontal scan rate         15:38 ~ 91:16Khz           Vertical scan rate         50 ~ 85(120 for 3D)Hz           Uniformity         75%           Screen size         0.71m ~ 7.73m (27.78" ~ 304.4") diagonal           Lamp info         Lamp           Light source type         Lamp           Lamp watts         203           Lamp life hours (up to)         6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)           Optical         Throw ratio         1.94:1 ~ 2.16:1           Projection distance (m)         1m - 12m           Zoom         1.1         1           Zoom (type)         Manual         4           Focal length (mm)         21.85 ~ 24           Native offset         115%         4           Connectivity         Inputs 1 × HDMI 1.4a 3D support, 1 × VGA (YPbPr/RGB), 1 × Composite video, 1 × Audio 3.5mm Outputs 1 × Audio 3.5mm Outputs 1 × Audio 3.5mm, 1 × USB-A power 1A           General         Noise level (typical)         27 dB           PC compatibility         FIND, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           T	Resolution	SVGA (800x600)
Native aspect ratio   4:3	Brightness	3,800 lumens
Native aspect ratio   4:3	Contrast ratio	22,000:1
V-/40°		
V-/40°		
Vertical Scan rate         15.38 ~ 91.15Khz           Vertical scan rate         50 ~ 85(120 for 3D)Hz           Uniformity         75%           Screen size         0.71m ~ 7.73m (27.78" ~ 304.4") diagonal           Lamp Info         Light source type           Lamp watts         203           Lamp life hours (up to)         6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)           Optical         Throw ratio           1 .94:1 ~ 2.16:1         2.00m           Projection distance (m)         1m - 12m           Zoom         1.1           Zoom type         Manual           Focal length (mm)         21.85 ~ 24           Native offset         115%           Connectivity         Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm, 1 x USB-A power 1A           General         Nise level (typical)         27dB           PC compatibility         FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           PC compatibility         FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           2D compatibility         FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           PC compatibility         Security Jayan, Kensington Lock, Password protected interface           OSD / display languages         25 langu		
Vertical scan rate         50 ~ 85(120 for 3D)Hz           Uniformity         75%           Screen size         0.71m ~ 7.73m (27.78" ~ 304.4") diagonal           Lamp info         Light source type           Lamp life hours (up to)         6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)           Optical         1.94:1 ~ 2.16:1           Throw ratio         1.94:1 ~ 2.16:1           Projection distance (m)         1m ~ 12m           Zoom         1.1           Zoom type         Manual           Focal length (mm)         21.85 ~ 24           Native offset         115%           Connectivity         Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm           Quiputs 1 x Audio 3.5mm, 1 x USB-A power 1A         Connectivity           General         1x Composite video, 1 x Audio 3.5mm, 1 x USB-A power 1A           General         27dB           Noise level (typical)         27dB           PC compatibility         PHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           2D compatibility         PHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           2D compatibility         PHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           2D compatibility         Security ar, Kensington Lock, Password protected interface <t< th=""><th></th><th>17 10</th></t<>		17 10
Uniformity         75%           Screen size         0.71m ~ 7.73m (27.78* ~ 304.4*) diagonal           Lamp info         Light source type           Lamp watts         203           Lamp life hours (up to)         6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)           Optical         1.94:1 ~ 2.16:1           Projection distance (m)         1m - 12m           Zoom         1.1           Zoom type         Manual           Focal length (mm)         21.85 ~ 24           Native offset         115%           Connectivity         Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm           Connectivity         Outputs 1 x Audio 3.5mm, 1 x USB-A power 1A           General         Noise level (typical)           Noise level (typical)         27dB           PC compatibility         FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           NTSC MJ, 3.58MHz, 4.45MHz Pab, BrD/GrHn/MN, 4.45M+z 480/M, 5.76k/p, 720p(50/60Hz), 1080(50/60Hz), 1080(50/60Hz), 30 D ready           Security         Security bar, Kensington Lock, Password protected interface           OSD / display languages         25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanaea, Norwegian, Pollsh, Portuguese, Romanian, Pussian, Chinese (simplified), Spanish, Swedish, Chinese (traditional)	Horizontal scan rate	15.38 ~ 91.15Khz
Uniformity   75%   Screen size   0.71m ~ 7.73m (27.78" ~ 304.4") diagonal	Vertical scan rate	
Screen size	Uniformity	*
Lamp info Light source type Lamp watts Lamp life hours (up to) 6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)  Optical Throw ratio 1.94:1 ~ 2.16:1 Projection distance (m) Im - 12m Zoom 1.1 Zoom type Manual Focal length (mm) 21.85 ~ 24 Native offset 115%  Connectivity Connections Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm, 1 x USB-A power 1A  General Noise level (typical) PC compatibility PC compa		
Lamp watts 203 Lamp life hours (up to) 6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)  Optical Throw ratio 1.94:1 ~ 2.16:1  Projection distance (m) 1m ~ 12m  Zoom 1.1  Zoom type Manual Focal length (mm) 21.85 ~ 24  Native offset 115%  Connectivity Connections Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm, 1 x USB-A power 1A  General Noise level (typical) 27dB PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac  Dompatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac  Dompatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac  Dompatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac  Security A, Kensington Lock, Password protected interface because of training the protected interface control Security Security bar, Kensington Lock, Password protected interface (traditional), Turkish, Vietnamese  Operating conditions S°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m  Remote control Card style Speaker count 1  Watts per speaker 10W In the box AC power cord Remote control Battery Basic user manual  Optional wireless models HDCast Pro, QuickCast Bundle, WHD200  Power  Power consumption (standy) Fower consumption (min) 187W		on the first (Entry diagonal
Lamp watts	-	lamp
Lamp life hours (up to)   6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)	*	•
Optical         1.94:1 ~ 2.16:1           Projection distance (m)         1m - 12m           Zoom         1.1           Zoom type         Manual           Focal length (mm)         21.85 ~ 24           Native offset         115%           Connectivity         Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm, 1 x USB-A power 1A           General         Nise level (typical)         27dB           PC compatibility         PHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           PC compatibility         NTSC MJ, 3.58MHz, 4.43MHz PAL B/D/G/H/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576/p, 720p(50/60Hz), 1080/(50/60Hz), 1080p(50/60Hz)           3D         3D ready           Security         Security bar, Kensington Lock, Password protected interface           OSD / display languages         25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese           Operating conditions         5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m           Remote control         Card style           Speaker count         1           Watts per speaker         10W           In the box         AC powe	·	
Throw ratio         1.94:1 ~ 2.16:1           Projection distance (m)         1m - 12m           Zoom type         Manual           Focal length (mm)         21.85 ~ 24           Native offset         115%           Connectivity            Connections            Outputs 1 x Audio 3.5mm, 1 x USB-A power 1A            27dB           PC compatibility         FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           2D compatibility         FHD, UXGA, SSGA, WXGA, HD, XGA, SVGA, VGA, Mac           3D         3D ready           Security bar, Kensington Lock, Password protected interface           OSD / display languages         25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguarian, Indonesian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese           Operating conditions         5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m           Remote control         Card style           Speaker count         1           Watts per speaker         10W           In the box         AC power cord Remote control Battery Basic user manual           Optional wireless models         HDCast Pr		0000 (Bright), 12000 (Byharrio), 10000 (Eco), 10000 (Eco+)
Projection distance (m)	•	1 94:1 2 16:1
Zoom type         Manual           Focal length (mm)         21.85 ~ 24           Native offset         11.5%           Connectivity         Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm, 1 x USB-A power 1A           General         Noise level (typical)         27 dB           PC compatibility         FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           2D compatibility         FHD, UXGA, SSMHz, 4.43MHz PAL B/D/G/HV/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.26/4.4MHz 480V/p, 576/p, 7209/60/60Hz), 1080p(50/60Hz), 1080p(50/60Hz)           3D         3D ready           Security         Security bar, Kensington Lock, Password protected interface           OSD / display languages         25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese           Operating conditions         5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m           Remote control         Card style           Speaker count         1           Watts per speaker         10W           In the box         AC power cord Remote control Battery Basic user manual         AC power cord Control Battery Basic user manual           Optional wireless models         HDCast Pro, QuickCast Bundle, WHD200           Power consumption (min)		
Zoom type		
Pocal length (mm)		
Native offset		
Connections  Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm, 1 x USB-A power 1A  General  Noise level (typical)  PC compatibility  PC compatibility  PHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac  2D compatibility  NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4,25/4.4MHz 480/p, 576/p, 720p(50/60Hz), 1080i(50/60Hz), 1080i(50/60Hz)  3D  3D 3D ready  Security Security Jar, Kensington Lock, Password protected interface  OSD / display languages  Poerating conditions  Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese  Operating conditions  F°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m  Remote control  Card style  Speaker count  1  Watts per speaker  10W  AC power cord Remote control Battery Basic user manual  Optional wireless models  HDCast Pro, QuickCast Bundle, WHD200  Power  Power consumption  (standby)  Power consumption (min)  187W		
Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm, 1 x USB-A power 1A		115%
General Noise level (typical)  PC compatibility	•	
General Noise level (typical) PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D 3D 3D ready Security Security Security bar, Kensington Lock, Password protected interface OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norvegian, Polish, Portuguese, Romanian, Russian, Chinese (ismplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese  Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m  Remote control Speaker count 1 Watts per speaker 10W AC power cord Remote control Battery Basic user manual  Optional wireless models HDCast Pro, QuickCast Bundle, WHD200  Power Power supply 100 ~ 240V, 50 ~ 60Hz Power consumption (standby) Power consumption (min) 187W	Connections	
Caperal   Noise level (typical)   27dB   PC compatibility   FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac   PD, Compatibility   NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)   3D ready   Security   Securi		
Noise level (typical)       27dB         PC compatibility       FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         2D compatibility       NTSC MJ, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)         3D       3D ready         Security       Security bar, Kensington Lock, Password protected interface         OSD / display languages       25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (isimplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese         Operating conditions       5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m         Remote control       Card style         Speaker count       1         Watts per speaker       10W         In the box       AC power cord Remote control Battery Basic user manual         Optional wireless models       HDCast Pro, QuickCast Bundle, WHD200         Power supply       100 ~ 240V, 50 ~ 60Hz         Power consumption (standby)       187W		Galpate 1 X/ladio o.omini, 1 X GGB // power 1//
PC compatibility PFID, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac D compatibility  NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)  D Security Security Security bar, Kensington Lock, Password protected interface  OSD / display languages Security Security bar, Kensington Lock, Password protected interface  OSD / display languages Security Security bar, Kensington Lock, Password protected interface  OSD / display languages Security Security bar, Kensington Lock, Password protected interface  OSD / display languages Security bar, Kensington Lock, Password protected interface  Security bar, Kensington, 1080p(50/60Hz)  Security bar, Kensington, 1080p(50/60Hz)  Security bas, Kensington, Lock, Password protected interface  Security bar, Kensington, 1080p(50/60Hz)  Security bar, Kensington, 1080p(50/6		07.10
Power consumption (min)  NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)  3D agay  Security Security bar, Kensington Lock, Password protected interface  OSD / display languages  25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese  Operating conditions  5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m  Remote control  Speaker count  1  Watts per speaker  10W  AC power cord  Remote control  Battery  Basic user manual  Optional wireless models  HDCast Pro, QuickCast Bundle, WHD200  Power  Power consumption  (standby)  Power consumption (min)  187W		
4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)  3D 3D ready  Security Security Lock, Password protected interface  OSD / display languages  25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese  Operating conditions  5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m  Remote control  Card style  Speaker count  1  Watts per speaker  10W  In the box  AC power cord Remote control Battery Basic user manual  Optional wireless models  HDCast Pro, QuickCast Bundle, WHD200  Power  Power consumption (standby)  Power consumption (min)  187W		
3D	2D compatibility	
3D       3D ready         Security       Security bar, Kensington Lock, Password protected interface         OSD / display languages       25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese         Operating conditions       5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m         Remote control       Card style         Speaker count       1         Watts per speaker       10W         In the box       AC power cord Remote control Battery Basic user manual         Optional wireless models       HDCast Pro, QuickCast Bundle, WHD200         Power       100 ~ 240V, 50 ~ 60Hz         Power consumption (standby)       187W		
Security Security bar, Kensington Lock, Password protected interface  OSD / display languages  25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese  Operating conditions  5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m  Remote control  Speaker count  1  Watts per speaker  10W  In the box  AC power cord  Remote control  Battery  Basic user manual  Optional wireless models  HDCast Pro, QuickCast Bundle, WHD200  Power  Power consumption  (standby)  Power consumption (min)  187W	3D	
OSD / display languages   25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese  Operating conditions   5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m  Remote control   Card style  Speaker count   1  Watts per speaker   10W  In the box   AC power cord   Remote control   Battery   Basic user manual  Optional wireless models   HDCast Pro, QuickCast Bundle, WHD200  Power   Power consumption   (standby)  Power consumption (min)   187W		· · · · · · · · · · · · · · · · · · ·
Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese  Operating conditions  5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m  Remote control  Speaker count  1  Watts per speaker  10W  AC power cord  Remote control  Battery  Basic user manual  Optional wireless models  HDCast Pro, QuickCast Bundle, WHD200  Power  Power consumption  (standby)  Power consumption (min)  187W	-	
Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese  Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m  Remote control Card style  Speaker count 1  Watts per speaker 10W In the box AC power cord Remote control Battery Basic user manual  Optional wireless models HDCast Pro, QuickCast Bundle, WHD200  Power  Power supply 100 ~ 240V, 50 ~ 60Hz Power consumption (standby)  Power consumption (min) 187W	OOD / Gispiay languages	
(traditional), Turkish, Vietnamese   Operating conditions   5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m		
Operating conditions         5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m           Remote control         Card style           Speaker count         1           Watts per speaker         10W           In the box         AC power cord Remote control Battery Basic user manual           Optional wireless models         HDCast Pro, QuickCast Bundle, WHD200           Power           Power supply         100 ~ 240V, 50 ~ 60Hz           Power consumption (standby)         0.5W           Power consumption (min)         187W		Russian, Chinese (simplified), Spanish, Swedish, Chinese
Remote control         Card style           Speaker count         1           Watts per speaker         10W           In the box         AC power cord Remote control Battery Basic user manual           Optional wireless models         HDCast Pro, QuickCast Bundle, WHD200           Power           Power supply         100 ~ 240V, 50 ~ 60Hz           Power consumption (standby)         0.5W           Power consumption (min)         187W		
Speaker count         1           Watts per speaker         10W           In the box         AC power cord Remote control Battery Basic user manual           Optional wireless models         HDCast Pro, QuickCast Bundle, WHD200           Power           Power supply         100 ~ 240V, 50 ~ 60Hz           Power consumption (standby)         0.5W           Power consumption (min)         187W	Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Watts per speaker  In the box  AC power cord Remote control Battery Basic user manual  Optional wireless models  HDCast Pro, QuickCast Bundle, WHD200  Power  Power supply 100 ~ 240V, 50 ~ 60Hz  Power consumption (standby)  Power consumption (min) 187W	Remote control	Card style
AC power cord Remote control Battery Basic user manual  Optional wireless models HDCast Pro, QuickCast Bundle, WHD200  Power  Power supply 100 ~ 240V, 50 ~ 60Hz  Power consumption (standby)  Power consumption (min) 187W	Speaker count	1
Remote control Battery Basic user manual  Optional wireless models HDCast Pro, QuickCast Bundle, WHD200  Power  Power supply 100 ~ 240V, 50 ~ 60Hz  Power consumption (standby)  Power consumption (min) 187W	Watts per speaker	10W
Battery   Basic User manual	In the box	
Basic user manual  Optional wireless models HDCast Pro, QuickCast Bundle, WHD200  Power  Power supply 100 ~ 240V, 50 ~ 60Hz  Power consumption (standby)  Power consumption (min) 187W		
Optional wireless models         HDCast Pro, QuickCast Bundle, WHD200           Power         100 ~ 240V, 50 ~ 60Hz           Power consumption (standby)         0.5W           Power consumption (min)         187W		·
Power         100 ~ 240V, 50 ~ 60Hz           Power consumption (standby)         0.5W           Power consumption (min)         187W	Ontional wireless models	
Power supply         100 ~ 240V, 50 ~ 60Hz           Power consumption (standby)         0.5W           Power consumption (min)         187W		FIDOGST FTO, QUIONOGST DUHUIC, WITIDZUU
Power consumption (standby)  Power consumption (min) 187W		100 ~ 240V 50 ~ 60Hz
(standby) Power consumption (min) 187W		
Power consumption (min) 187W		U.UVV
		187W
Power consumption (max) 225W		

3kg

316 x 244 x 108



