

Samples - M40-HYBRID/MUSTERSET - 1627060


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



M40 Hybrid sample set, SB series, consisting of cable connector, straight device connector, and sample cable



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 298795
GTIN	4055626298795
Weight per Piece (excluding packing)	772.000 g
Custom tariff number	90230080
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

General

Type of locking	SPEEDCON locking
Direction of rotation of contact chamber numbering	Standard
Coding	CAT5, coding 1
Contact connection method	Crimp connection
Number of positions	13
Contact diameter of power contacts	3.6 mm
Litz wire cross section of power contacts min.	1 mm ²
Litz wire cross section of power contacts max.	16 mm ²
Rated current for power contacts	70 A
Contact diameter of signal contacts	1 mm
Litz wire cross section of signal contacts min.	0.06 mm ²
Litz wire cross section of signal contacts max.	1.5 mm ²
Nominal current per signal contact	8 A

Samples - M40-HYBRID/MUSTERSET - 1627060

Technical data

General

Contact diameter, data contacts	0.8 mm
Litz wire cross section, data contacts, min.	0.08 mm ²
Litz wire cross section, data contacts, max.	0.5 mm ²
Rated current	3.6 A
Pg housing screw connection	none

Ambient conditions

Degree of protection	IP67
----------------------	------

Specifications according to DIN EN 61984:2001

Nominal / operating voltage of power contacts	630 V AC
Rated surge voltage of power contacts	6 kV
Overvoltage category of power contacts	III
Degree of pollution of power contacts	3
Nominal / operating voltage of signal contacts	500 V
Rated surge voltage of signal contacts	1.5 kV
Overvoltage category of signal contacts	III
Degree of pollution of signal contacts	3


Environmental Product Compliance

	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Samples - M40-HYBRID/MUSTERSET - 1627060

Schematic diagram



Pin assignment of pin, CAT5

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260708
eCl@ss 7.0	27440312
eCl@ss 8.0	27440102
eCl@ss 9.0	27440103

Samples - M40-HYBRID/MUSTERSET - 1627060

Classifications

ETIM

ETIM 5.0	EC002635
ETIM 6.0	EC002061