

Starter kit - ILC 131 STARTERKIT - 2701835

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



ILC 131 starter kit incl. ILC 131 ETH, control panel, power supply unit, plus accessories and cables with test application set up

Product Description

Test the highly communicative ILC 131 ETH high-performance controller. Small to medium function units can be automated inexpensively using this high-performance controller. The high-performance controller features modular expansion, easy programming, and high performance. We have compiled this starter kit so that you can try out the capabilities of the ILC 131 ETH for yourself. It has digital and analog output and input terminals as well as simulation modules. In addition, example projects for PC WORX EXPRESS and the web server are available to the user.

Your advantages

- ✓ Integrated I/Os: 8/4
- Processing time per 1000 instructions: 90 µs (bit data types), 1.7 ms (mixed data types)
- ☑ Program/mass storage: 192 KB/192 KB
- ☑ Retentive mass storage: 8 KB
- ✓ Supply voltage: 24 V DC







Key Commercial Data

| Packing unit | 1 pc |
|--------------------------------------|--------------------------------|
| GTIN | 4 046356 858588 |
| GTIN | 4046356858588 |
| Weight per Piece (excluding packing) | 2,100.000 g |
| Custom tariff number | 85371091 |
| Country of origin | Germany |
| Note | Made to Order (non-returnable) |

Technical data

Environmental Product Compliance

| REACh SVHC | 1,2-dimethoxyethane,ethylene glycol dimethyl ether (EGDME) 110-71-4 |
|------------|---|
| | Lead 7439-92-1 |



Starter kit - ILC 131 STARTERKIT - 2701835

Technical data

Environmental Product Compliance

| China RoHS | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |
|------------|--|
| | 9 , |

Articles in set

Controller - ILC 131 ETH - 2700973



The Inline controller offers the option of communicating via PROFINET and Modbus/TCP. Programming is carried out using PC Worx Express or PC Worx (IEC 61131-3).

Inline ME terminal - IB IL AI 2/SF-ME - 2863944



Inline, Analog input terminal, Analog inputs: $2, 0 \ V \dots 10 \ V, -10 \ V \dots 10 \ V, 0 \ mA \dots 20 \ mA, 4 \ mA \dots 20 \ mA, -20 \ mA \dots 20 \ mA, connection method: <math>2$ -wire, transmission speed in the local bus: $500 \ kbps$, degree of protection: IP20, including Inline connector and labeling field

Interface module - UM 45-IB-DI/SIM8 - 2962997



VARIOFACE switch module, with COMBICON connector, for simulation, for 8 signals, for mounting DIN rail NS 35

Software - PC WORX EXPRESS - 2988670



PC WORX EXPRESS is a piece of easy-to-operate engineering software. Class 100 and class 1000 modular small-scale controllers as well as the PC WORX SRT software controller with IEC-61131 programming languages ST and LD are supported. Free programming version without licensing mechanism, max. 128 kbyte of input and output data.

Classifications

eCl@ss

| eCl@ss 4.0 | 27250200 |
|------------|----------|
| eCl@ss 4.1 | 27240600 |
| eCl@ss 5.0 | 27242700 |
| eCl@ss 5.1 | 27242700 |



Starter kit - ILC 131 STARTERKIT - 2701835

Classifications

eCl@ss

| eCl@ss 6.0 | 27242200 |
|------------|----------|
| eCl@ss 7.0 | 27242207 |
| eCl@ss 8.0 | 27242219 |
| eCl@ss 9.0 | 27242219 |

ETIM

| ETIM 3.0 | EC000236 |
|----------|----------|
| ETIM 4.0 | EC002581 |
| ETIM 5.0 | EC002581 |
| ETIM 6.0 | EC002581 |
| ETIM 7.0 | EC002581 |

UNSPSC

| UNSPSC 6.01 | 43172015 |
|---------------|----------|
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11 | 43172018 |
| UNSPSC 12.01 | 43201404 |
| UNSPSC 13.2 | 39122114 |
| UNSPSC 19.0 | 39122114 |

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC EAC-Zulassung

Phoenix Contact 2020 © - all rights reserved http://www.phoenixcontact.com