

Power supply unit - FB-PS-MB-25DSUB/EX - 2316146

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Four-channel, redundant fieldbus power supply base. Host connection is a D-SUB 25 socket connector.



Product Description


Universal four-channel, redundant fieldbus power supply base with D-SUB 25 host connector.

Your advantages

- Redundancy
- Built-in relay diagnostics



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 128351
GTIN	4055626128351
Custom tariff number	85366990
Country of origin	United States
Note	Made to Order (non-returnable)

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	180 mm
Height	77 mm
Depth	180 mm

Ambient conditions

Power supply unit - FB-PS-MB-25DSUB/EX - 2316146

Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	95 % (non-condensing)
Degree of protection	IP20

General

Net weight	0 g
Conformance	CE-compliant
Fieldbus Foundation	FF-831

Power supply

Conductor cross section flexible max.	2.50 mm ²
Conductor cross section flexible min.	0.20 mm ²
Conductor cross section solid max.	2.50 mm ²
Conductor cross section solid min.	0.20 mm ²
Conductor cross section AWG max.	12
Conductor cross section AWG min.	30

Interfaces

Interface 1	Invensys DCS cabling system
Interface	Host system
Number of connections	1
Connection method	D-SUB-25 female connector
Inductance Li	17.8 mH (trunk and host)
Max. output voltage U _o	30 V DC (trunk and host)

Digital outputs

Output name	Alarm
-------------	-------

Standards and Regulations

Type of test	Corrosive resistance in acc. to ANSI-ISA 71.04-1985 - Severity level G3
Designation	Standards/regulations
Standards/regulations	Ring wave noise immunity in acc. with IEC 61000-4-12
Designation	Standards/regulations
Standards/regulations	Dry heat in acc. with IEC 61131-2
Designation	Standards/regulations
Standards/regulations	Damp heat in acc. with IEC 61131-2
Designation	Standards/regulations
Standards/regulations	Shock and vibration in acc. with EN 61131-2 and EN 50178
	IEC 61158-2
	NE21
	EN 61326
Conformance	CE-compliant

Power supply unit - FB-PS-MB-25DSUB/EX - 2316146

Technical data

Standards and Regulations

Fieldbus Foundation	FF-831
ATEX	Sira 11ATEX4216X; II 3 G Ex nA nC IIC T4 Gc
IECEX	IECEX SIR 11.0097X; Ex nA nC IIC T4 Gc
CSA, USA/Canada	Class I, Div. 2, Groups A, B, C, D; Ex nA nC IIC T4 Class I, Zone 2, AEx nA nC IIC T4

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 10.0.1	27242692
eCl@ss 5.1	27242600
eCl@ss 6.0	27242600
eCl@ss 7.0	27242611
eCl@ss 8.0	27242611
eCl@ss 9.0	27242692

ETIM

ETIM 4.0	EC002583
ETIM 5.0	EC001598
ETIM 6.0	EC002584
ETIM 7.0	EC002584

Accessories

Spare parts

Power module - FB-PS-PLUG-24DC/28DC/0.5/EX - 2316132



Power supply plug for fieldbus system in hazardous locations. Provides 500 mA @ 28 V DC to couplers along the trunk.