

Mini Cool Edge 0.60mm Connectors

MEETS SFF-TA-1002, GEN Z, EDSFF AND OCP NIC 3.0 SPECIFICATIONS

Mini Cool Edge is a 0.60mm high density, high speed card edge connector for new generation small form factor system. This fine pitch solution offers multiple BTB applications like right angle, mezzanine and coplanar and support cable interconnect options.

Mini Cool Edge 0.60mm meets SFF-TA-1002, Gen Z, EDSFF and OCP NIC 3.0 specifications.

- Common applications include Solid State Drive, Network Interface Card, Add-In Card.
- Vertical, right angle, straddle mount and orthogonal options are available
- High Speed from 32GT/s to 56GT/s, and up to 112GT/s PAM4



FEATURES

- Signal pin pitch at 0.60mm with current rating of 1.1A, up to 12 pins for power application
- Signal pins options from 56, 84, 140, 168, 280
- Customization of pin count upon request
- Small form factor
- Discrete pin design
- Supports 1.6mm thick mating board

BENEFITS

- Supports small power BTB applications
- Provides power for module card
- Supports different board-to-board, module applications like FPGA, SSD, NIC
- Serves as a space-saving connector
- Supports single-ended, high speed differential pairs up to 32G NRZ, 56G PAM4, 112G PAM4
- For most standard BTB applications

Mini Cool Edge 0.60mm Connectors

TECHNICAL INFORMATION

MATERIAL

- Contact Base Metal: Copper Alloy
- Contact Area Finish: Gold over Nickel
- Solder Area Finish: Tin over Nickel
- Housing: High temperature thermoplastic (UL 94V-0)

ELECTRICAL PERFORMANCE

- Contact Resistance: 30mΩ max. initial; 15mΩ max. change after test
- Power Supply: 72W max.
- Dielectric Withstanding Voltage: 300VDC

MECHANICAL PERFORMANCE

- Durability: 200 mating cycles
- Mating Force: 0.75N/pin max.
- Unmating Force: 0.12N/pin min.

SPECIFICATIONS

- Amphenol Product Specification: S-ME-001

PACKAGING

- Orthogonal: Tube
- Straddle mount: Tray

ENVIRONMENTAL

- Humidity: 500 hours, 25±3°C at 80% ~95% RH. Per EIA 364-31B Method III
- Temperature Life: 105±2°C for 168 hours. Per EIA 364-17
- Thermal Shock: 5 cycles between -55°C to +85°C. Per EIA 364-32
- Mixed Flow Gas: 10 days to simulate 7 years field life. EIA364-65 class IIA

TOOLING INFORMATION

- Special pin count option available upon request

TARGET MARKETS/APPLICATIONS



Baseband
Commercial Systems
Networking
Radio Units



High-end Computing System
Server and Storage Systems

PART NUMBERS

Description	Part Numbers	Gen Z	EDSFF	OCP NIC 3.0
Mini Cool Edge 0.60mm 56 signal pins, SMT, Vertical	ME1005610101011	✓	✓	
Mini Cool Edge 0.60mm 84 signal pins, SMT, Vertical	ME1008410101011	✓	✓	
Mini Cool Edge 0.60mm 140 signal pins, SMT, Vertical	ME1014010101011	✓	✓	
Mini Cool Edge 0.60mm 168 signal pins, SMT, Vertical	ME1016810101011			✓
Mini Cool Edge 0.60mm 280 signal pins, SMT, Vertical	ME1028040101011	✓		
Mini Cool Edge 0.60mm 56 signal pins, SMT, Right angle, Seating height 3.05mm	ME1005610201011	✓		
Mini Cool Edge 0.60mm 84 signal pins, SMT, Right angle, Seating height 3.05mm	ME1008410201011	✓		
Mini Cool Edge 0.60mm 140 signal pins, SMT, Right angle, Seating height 3.05mm	ME1014010201011	✓		
Mini Cool Edge 0.60mm 56 signal pins, SMT, Right angle, Seating height 4.05mm	ME1005610201031		✓	
Mini Cool Edge 0.60mm 84 signal pins, SMT, Right angle, Seating height 4.05mm	ME1008410201031		✓	
Mini Cool Edge 0.60mm 140 signal pins, SMT, Right angle, Seating height 4.05mm	ME1014010201031		✓	✓
Mini Cool Edge 0.60mm 168 signal pins, SMT, Right angle, Seating height 4.05mm	ME1016810201031			✓
Mini Cool Edge 0.60mm 56 signal pins, SMT, OCP, Straddle mount, 1.6mm PCB, 0.0mm offset	ME1005613401101	✓	✓	
Mini Cool Edge 0.60mm 56 signal pins, SMT, OCP, Straddle mount, 2.36mm PCB, 0.0mm offset	ME1005613401201	✓	✓	
Mini Cool Edge 0.60mm 84 signal pins, SMT, OCP, Straddle mount, 1.6mm PCB, 0.0mm offset	MET008431401101	✓	✓	
Mini Cool Edge 0.60mm 140 signal pins, SMT, OCP, Straddle mount, 1.6mm PCB, 0.0mm offset	ME1014013401101	✓	✓	✓
Mini Cool Edge 0.60mm 140 signal pins, SMT, OCP, Straddle mount, 1.93mm PCB, -0.3mm offset	ME1014013401311	✓	✓	✓
Mini Cool Edge 0.60mm 140 signal pins, SMT, OCP, Straddle mount, 2.36mm PCB, 0.0mm offset	ME1014013401201	✓	✓	✓
Mini Cool Edge 0.60mm 168 signal pins, SMT, OCP, Straddle mount, 1.6mm PCB, 0.0mm offset	ME1016813401101			✓
Mini Cool Edge 0.60mm 168 signal pins, SMT, OCP, Straddle mount, 1.93mm PCB, -0.3mm offset	ME1016813401311			✓
Mini Cool Edge 0.60mm 168 signal pins, SMT, OCP, Straddle mount, 2.36mm PCB, 0.0mm offset	ME1016813401201			✓
Mini Cool Edge 0.60mm 168 signal pins, SMT, OCP, Straddle mount, 2.6mm PCB, 0.0mm offset	ME1016833400701			✓
Mini Cool Edge 0.60mm 56 signal pins, 1x1, Press-fit, Orthogonal	ME2005602311011		✓	
Mini Cool Edge 0.60mm 56 signal pins, 1x4, Press-fit, Orthogonal	ME2005602311041		✓	

SS10MINIC00L0519EA4