



USB-C to USB Type-B Cable (M/M) - USB 3.1, Gen 2 (10 Gbps), Thunderbolt 3 Compatible, 20-in.

MODEL NUMBER: U422-20N-G2











Connects a printer, hub or other USB-B device to your laptop, MacBook, Chromebook or Ultrabook's USB-C or Thunderbolt 3 port.

Features

Connects a USB-B Printer, Scanner or External Hard Drive to Your Laptop's USB-C Port
This USB-C to USB 3.0 Type-B cable allows you to connect a printer, scanner, hard drive, docking station, optical drive or other existing USB-B peripheral to any device with a USB-C or Thunderbolt 3 port, including MacBooks, Ultrabooks and Chromebooks. Its 20-inch length makes it easy to carry in your briefcase or laptop bag for quick downloads and file transfers on the go.

Transfers Data and Charges Devices at Lightning-Fast USB 3.1 Gen 2 Speeds

The USB Type-C to USB 3.0 Type-B cable supports USB 3.1 Gen 2 data transfer rates up to 10 Gbps, which is double the speed of USB 3.1 Gen 1.

Reversible USB-C Connector Attaches in Either Direction

Unlike traditional USB cables that connect in only one direction, the reversible USB-C male connector plugs into a USB-C or Thunderbolt 3 port in either direction for a fumble-free connection every time.

Highlights

- USB-C to USB 3.0 Type-B cable compatible with USB-B, USB-C and Thunderbolt 3 devices
- Supports USB 3.1 Gen 2 speeds up to 10 Gbps to ensure lightning-fast data transfers
- Reversible USB-C plug connects in either direction for immediate no-fuss use
- Plug-and-play operation with no software required for easy, immediate installation

Applications

- Connect a printer or scanner to the USB-C or Thunderbolt 3 port on your computer or laptop
- Charge and sync a USB-C or Thunderbolt 3 mobile device from a USB-B wall charger up to 20 in. away
- Connect your laptop to a docking station or hub with a USB-B port

System Requirements

- Devices with USB-C or Thunderbolt 3 ports
- Devices with USB-B ports
- USB 3.1 Gen 2 compatibility required in both connected devices to achieve USB 3.1 Gen 2 speeds

Package Includes

 U422-20N-G2 USB-C 3.1 Gen 2 to USB 3.0 Type-B Cable (M/M), 20 in.



Specifications

UPC Code			
INPUT	OVERVIEW		
Cable Length (ft.) 1.7 Cable Length (m) 0.5 Cable Length (in.) 20 Cable Length (cm) 50.8 PHYSICAL Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 4.5MM Color Black Material of Construction PVC Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 185 F (-20 to 85 C) Relative Humidity 10 to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB B (MALE) Connector Plating Nickel Contact Plating Gold			
Cable Length (m) 0.5 Cable Length (in.) 20 Cable Length (cm) 50.8 PHYSICAL Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 4.5MM Color Black Material of Construction PVC Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 185 F (-20 to 85 C) Relative Humidity 10 to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB B (MALE) Connector Plating Gold FEATURES & SPECIFICATIONS			
Cable Length (in.) 20 Cable Length (cm) 50.8 PHYSICAL Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 4.5MM Color Black Material of Construction PVC Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 185 F (-20 to 85 C) Relative Humidity 10 to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB B (MALE) Connector Plating Gold FEATURES & SPECIFICATIONS			
Cable Length (cm) 50.8 PHYSICAL Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 4.5MM Color Black Material of Construction PVC Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 185 F (-20 to 85 C) Relative Humidity 10 to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB B (MALE) Connector Plating Oold FEATURES & SPECIFICATIONS			
PHYSICAL Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 4.5MM Color Black Material of Construction PVC Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 185 F (-20 to 85 C) Relative Humidity 10 to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB B (MALE) Connector Plating Gold FEATURES & SPECIFICATIONS			
Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 4.5MM Color Black Material of Construction PVC Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 185 F (-20 to 85 C) Relative Humidity 10 to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB B (MALE) Connector Plating Gold FEATURES & SPECIFICATIONS			
Cable Outer Diameter (OD) 4.5MM Color Black Material of Construction PVC Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 185 F (-20 to 85 C) Relative Humidity 10 to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB B (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS	PHYSICAL		
Color Black Material of Construction PVC Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 185 F (-20 to 85 C) Relative Humidity 10 to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB B (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS			
Material of Construction PVC Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 185 F (-20 to 85 C) Relative Humidity 10 to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB B (MALE) Connector Plating Nickel Contact Plating Gold			
Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 185 F (-20 to 85 C) Relative Humidity 10 to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB B (MALE) Connector Plating Nickel Contact Plating Gold			
ENVIRONMENTAL Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 185 F (-20 to 85 C) Relative Humidity 10 to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB B (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS			
Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 185 F (-20 to 85 C) Relative Humidity 10 to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB B (MALE) Connector Plating Nickel Contact Plating Gold			
Storage Temperature Range -4 to 185 F (-20 to 85 C) Relative Humidity 10 to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB B (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS			
Relative Humidity 10 to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB B (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS			
CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB B (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS			
Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB B (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS			
Side B - Connector 1 USB B (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS			
Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS			
Contact Plating Gold FEATURES & SPECIFICATIONS			
FEATURES & SPECIFICATIONS			
USB Specification USB 3.1 Gen 2 (up to 10 Gbps)			
Technology USB; USB 3.0 (SuperSpeed); USB 3.1 (Gen 1); USB 3.1 (Gen 2)			
CERTIFICATIONS			
Certifications Tested to RoHS, REACH			



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies