# Product datasheet Characteristics

## LJ7K06Q7

TeSys LJ - enclosed DOL starter - 6 A - 24 V AC coil



N	12	ıır
ıv	ıc	ш

Range	TeSys	
Product name	TeSys LJ	
Device short name	LJ7K	
Product or component type	Enclosed DOL starter	
Device application	Safety	
Utilisation category	AC-3	
Device composition	Circuit-breaker ordered separately Contactor Control transformer	:
[le] rated operational current	6 A AC-3	
[Uc] control circuit voltage	24 V AC 50/60 Hz	
Control type	Push-button start white I Push-button stop black O Mushroom head push-button emergency stop red	

#### Complementary

Cable entry number	4 2 Pg 13 + 2 Pg 16 top 4 2 Pg 13 + 2 Pg 16 bottom	
Width	175 mm	
Height	165 mm	
Depth	177 mm	

#### **Environment**

Littiioiii		SE
Standards	IEC 60947-4-1 IEC 60204-1	itended 6
Material	Polycarbonate	not ir
IP degree of protection	IP55 conforming to IEC 60529	
IK degree of protection	IK07 conforming to IEC 60529	entati
Environmental characteristic	Standard environment	ocum.

### Offer Sustainability

REACh free of SVHC	Yes
--------------------	-----

EU RoHS Directive	Compliant EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Contractual warranty		

Warranty	18 months