



Main

| | |
|------------------------------|---|
| Range of product | TeSys F TeSys D TeSys D control relay |
| Range | TeSys |
| Device short name | LADN |
| Product or component type | Auxiliary contact block |
| Range compatibility | TeSys D LC1D contactor |
| Auxiliary contacts operation | Instantaneous |
| Pole contact composition | 1 NO + 1 NC |
| Connections - terminals | lugs-ring terminals |

Complementary

| | |
|---|--|
| Mounting location | Front |
| [Ui] rated insulation voltage | 600 V UL 690 V IEC 60947-5-1 600 V CSA |
| [Ue] rated operational voltage | 690 V AC 25..400 Hz |
| [Ith] conventional free air thermal current | 10 A 140 °F (60 °C) |
| Irms rated making capacity | 140 A AC 250 A DC |
| Permissible short-time rating | 100 A 140 °F (60 °C) 1 s 120 A 140 °F (60 °C) 500 ms 140 A 140 °F (60 °C) 100 ms |
| Protection type | GG fuse 10 A rating according to operational current for Ue <= 690 V |
| Associated fuse rating | 10 A gG IEC 60947-5-1 |
| Mechanical durability | 30 Mcycles |
| Minimum switching current | 5 mA |

| | |
|---------------------------|---|
| Minimum switching voltage | 17 V |
| Non-overlap time | 1.5 ms on de-energisation no overlap between NC and NO contact 1.5 ms on energisation no overlap between NC and NO contact |
| Overlap time | 1.5 ms |
| Insulation resistance | > 10 MOhm |

Environment

| | |
|---------------------------------------|---|
| Environmental characteristic | Normal environment |
| Standards | BS 4794 IEC 60947-5-1 VDE 0660 EN 60947-5-1 NF C 63-140 |
| Product certifications | CSA UL |
| IP degree of protection | IP2x VDE 0106 |
| Protective treatment | TH IEC 60068 |
| Ambient air temperature for operation | -40...158 °F (-40...70 °C) |
| Ambient air temperature for storage | -76...176 °F (-60...80 °C) |
| Operating altitude | 9842.52 ft (3000 m) without |

Ordering and shipping details

| | |
|-------------------|---------------------------------|
| Category | 22341 - CONTACTOR,D,K,&F ACCESS |
| Discount Schedule | I12 |
| GTIN | 00785901603313 |
| Returnability | No |
| Country of origin | FR |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|