Product data sheet Characteristics

LADN313

TeSys D - auxiliary contact block - 3 NO + 1 NC - spring terminals

Product availability: Non-Stock - Not normally stocked in distribution facility





Main

Range of product	TeSys D control relay	
	TeSys D	
Range	TeSys	
Device short name	LADN	
Product or component type	Auxiliary contact block	
Range compatibility	TeSys D CR1F contactor	
Auxiliary contacts operation	Instantaneous	
Pole contact composition	3 NO + 1 NC	
Connections - terminals	spring terminals 2 0.00 in ² (2.5 mm ²)flexible without cable end	
	spring terminals 2 0.00 in ² (2.5 mm ²)solid without cable end	

Complementary

o in promontary		-
Mounting location	Front	
[Ui] rated insulation voltage	600 V UL 690 V IEC 60947-5-1 600 V CSA	
[Ue] rated operational voltage	690 V AC 25400 Hz	
[lth] conventional free air thermal current	10 A 140 °F (60 °C)	
Irms rated making capacity	140 A AC 250 A DC	,
Permissible short-time rating	100 A 140 °F (60 °C) 1 s 120 A 140 °F (60 °C) 500 ms 140 A 140 °F (60 °C) 100 ms	
Protection type	GG fuse 10 A rating according to operational current for Ue <= 690 V	
Associated fuse rating	10 A gG IEC 60947-5-1	
Mechanical durability	30 Mcycles	F F
Minimum switching current	5 mA	

Minimum switching voltage	17 V
Non-overlap time	1.5 ms on de-energisation no overlap between NC and NO contact 1.5 ms on energisation no overlap between NC and NO contact
Overlap time	1.5 ms
Insulation resistance	> 10 MOhm
Net weight	0.11 lb(US) (0.05 kg)

Environment

Environmental characteristic	Normal environment
Standards	EN 60947-5-1
	BS 4794
	NF C 63-140
	IEC 60947-5-1
	VDE 0660
Product certifications	UL
	CSA
IP degree of protection	IP2x VDE 0106
Protective treatment	TH IEC 60068
Ambient air temperature for operation	-40158 °F (-4070 °C)
Ambient air temperature for storage	-76176 °F (-6080 °C)
Operating altitude	9842.52 ft (3000 m) without

Ordering and shipping details

22341 - CONTACTOR,D,K,&F ACCESS
l12
00785901221142
No
FR

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

Contractual warranty

Warranty	18 months