

Polyimide Film ESD Tapes multicomp^{PRO}

RoHS
Compliant

Polyimide Film Tape with Polyimide

Polyimide film and silicone adhesive used for PCB solder masking and other high temperature applications. This product is amber colored and 2.7 mil (69 microns) thick.

Features

- The polyimide film does not soften at elevated temperatures, thus the film provides an excellent release surface at elevated temperatures
- Dimensionally stable at high temperatures, which helps reduce rework, helping to enable high productivity
- Flame retardant, chemical and radiation resistant which helps protect surfaces to help reduce replacement costs
- The silicone adhesive's high temperature performance helps reduce adhesive transfer which helps to eliminate cleaning, enabling high productivity.
- Polyethylene tape core instead of cardboard.
- Low Static Polyimide Film overcomes this problem without any of the typical drawbacks of conventional "anti-static" or "static-free" tapes (e.g., Variable adhesion and opaqueness)."

Polyimide Film Tape

Backing : Polyimide
Adhesive : Silicone
Colour : Amber
Standard Roll Length : 33meters (36yd)

Physical Properties

Adhesion to Steel	6 N / Inch	D-3330
Tensile Strength at Break	150 N / Inch	D-3579
Elongation at Break	0.62	D-3579
Backing Thickness	0.025MM	D-3652
Total Tape Thickness	0.07MM	D-3652
Temperature Use Range	-70° to -260°	-
Dielectric Strength	7000 volts	D-149
Flame Retardancy	UL510	-
Static Charge: (measured at Removal from roll: 50% RH, 70°F (25°C) in an Removal from PWB: ESD controlled environment)	<200 volts <100 volts	-

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp^{PRO}

Polyimide Film ESD Tapes multicomp^{PRO}

Silicone adhesive High temperature performance helps reduce Virtually no cleaning required adhesive transfer helps increase productivity

High adhesive to Helps reduce adhesive transfer Virtually no cleaning required

Storage and Shelf Life

It can be stored for 12 months keeping in dark place with 50% humidity at 25°

Part Number Table

Description	Part Number
Polyimide Film ESD Tape, Amber, 25mm × 33m	MP003347
Polyimide Film ESD Tape, Amber, 19mm × 33m	MP003348
Polyimide Film ESD Tape, Amber, 12mm × 33m	MP003349
Polyimide Film ESD Tape, Amber, 6.35mm × 33m	MP003350

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp^{PRO}