Polyimide Film Tapes



RoHS Compliant

Polyimide Film Tape with Polyimide

Polyimide film and silicone adhesive used for PCB solder masking and other high temperature applications. This product is amber Colored and 2.7 mil (69 microns) thick.

Features

- The polyimide film does not soften at elevated temperatures, thus the film provides an excellent release surface at elevated temperatures
- Dimensionally stable at high temperatures, which helps reduce rework, helping to enable high productivity
- · Flame retardant, chemical and radiation resistant which helps protect surfaces to help reduce replacement costs
- The silicone adhesive's high temperature performance helps reduce adhesive transfer which helps to eliminate cleaning, enabling high productivity
- · Polyethylene tape core instead of cardboard
- · Polyimide Film with UL 510 flame retardant.

Polyimide Film Tape

Backing : Polyimide
Adhesive : Silicone
Colour : Amber

Standard Roll Length : 33meters (36yd)

Physical Properties

Adhesion to Steel	6 N / Inch	D-3330
Tensile Strength at Break	150 N / Inch	D-3579
Elongation at Break	0.62	D-3579
Backing Thickness	0.025 mm	D-3652
Total Tape Thickness	0.07 mm	D-3652
Temperature Use Range	-70° to -260°	-
Dielectric Strength	7000 volts	D-149
Flame Retardancy	UL510	-

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



Polyimide Film Tapes



Silicone adhesive High temperature performance helps reduce Virtually no cleaning required adhesive transfer helps increase productivity

High adhesive to Helps reduce adhesive transfer Virtually no cleaning required

Storage and Shelf Life

It can be stored for 12 months keeping in dark place with 50% humidity at 25°

Part Number Table

Description	Part Number
Polyimide Film Tape, Amber, 25mm × 33m	MP003352
Polyimide Film Tape, Amber, 9.5mm × 33m	MP003353
Polyimide Film Tape, Amber,19mm × 33m	MP003354
Polyimide Film Tape, Amber, 6.35mm × 33m	MP003355
Polyimide Film Tape, Amber, 12mm × 33m	MP003356

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

