

Power strips used within the patient care vicinity may be permanently attached so that it is only removable with a tool. Choose the PSCLAMP for a safe and secure mounting solution.

For Patient-Care Vicinity: UL 60601-1 Medical-Grade Power Strip with Surge Protection, 4 Hospital-Grade Outlets, 6 ft. Cord

MODEL NUMBER: SPS406HGULTRA



Full 60601-1 compliance and agency listing, surge protection, integrated locking safety covers and a 6 ft. cord make this medical-grade power strip ideal for standalone use in areas inside and outside patient-care vicinities.

Description

The SPS406HGULTRA Medical-Grade Power Strip -- patent #7,375,939 and 8,339,759 -- is designed and listed to full 60601-1 and 60950-1 compliance, making it ideal for standalone use in all patient care vicinities, therapy rooms, imaging environments, laboratories and administrative areas.

This 120V, 60 Hz power strip features a NEMA 5-15P-HG hospital-grade plug and four NEMA 5-15R-HG hospital-grade outlets that include integrated locking safety covers. Plus, 1410 joules of surge suppression prevent dangerous power spikes that can damage connected equipment and destroy data. A 15A resettable circuit breaker also protects your equipment from overloads. An LED indicator tells you power is present and protected from surges (with no ground faults or line/neutral reversals).

The power strip is protected by a patented antimicrobial powder coating with EPA-registered and FDA-compliant silver ionic technology. The antimicrobial surface protection is 99.9 percent effective in inhibiting the growth of bacteria, such as C. diff and MRSA, and reducing the risk of HAIs in hospitals and other medical environments. The coating meets the requirements of JIS Z 2801:2000, an international standard for evaluating efficacy in antimicrobial products.

Mounting slots and flanges let you install the SPS406HGULTRA on a wide variety of surfaces. The all-metal housing ensures safety and is guaranteed to stand up to demanding environments.

With a switchless design that prevents accidental shutoff and a six-foot power cord that provides flexibility in placing the power strip, the SPS406HGULTRA is a recommended replacement for all non-compliant power strips.

Highlights

- Patented antimicrobial coating
99.9% effective in inhibiting bacteria and viruses
- Approved for standalone use in all patient-care vicinities
- Listed to UL 60601-1 and UL 60950-1 specifications
- 1410 joules of surge suppression
- Automatic single-fault detection for added patient protection

Package Includes

- SPS406HGULTRA UL 60601-1 Medical-Grade Power Strip
- Owner's manual



Features

Power Distribution Anywhere in Any Medical Facility

- Ideal for standalone use in all patient-care vicinities, therapy rooms, imaging environments, laboratories and administrative areas
- 120V, 50/60 Hz power strip complies with UL 60601-1 and UL 60950-1 specifications
- Automatic single-fault protection
- Tested to CAN/CSA-C22.2 No. 601.1-M90 and 60950-1-03 Canadian standards
- Patent # 7,375,939 & 8,339,759

Exclusive, Patented Antimicrobial Protection

- Silver ionic powder coating is 99.9% effective in inhibiting the growth of bacteria like C. diff and MRSA
- Patented coating helps to reduce the risk of healthcare-acquired infections (HAIs) in hospitals and other medical environments
- Coating meets the requirements of JIS Z 2801:2000, an international standard for evaluating efficacy in antimicrobial products

Versatile Medical-Grade Solution

- 4 NEMA 5-15R-HG hospital-grade outlets provide consistent power
- 6 ft. power cord with NEMA 5-15P-HG plug provides ample reach to the power source
- Rugged all-metal housing for long life in demanding environments

Premium Safety Features

- 1410 joules of surge suppression protect against dangerous power spikes
- Integrated locking outlet safety covers block access to unused outlets
- Built-in 15A resettable circuit breaker protects against dangerous overloads
- Switchless design prevents accidental shut-off
- LED indicates power is present and surge-protected

Ready to Use Right Out of the Box

- Built-in mounting slots and flanges for easy installation on a variety of surfaces

Specifications

OVERVIEW	
UPC Code	037332194091
OUTPUT	
Frequency Compatibility	60 Hz
Output (Watts)	1800
Output Receptacles	(4) 5-15R-HG
Circuit Breaker (amps)	15



Overload Protection	15A resettable circuit breaker
Outlet Orientation	Single row of 4
Right-Angle Outlets	No
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	15A 120V
Voltage Compatibility (VAC)	120
Maximum Surge Amps	60000
Input Plug Type	NEMA 5-15P-HG
Input Cord Length (ft.)	6
Right-Angle Plug	No
Input Cord Length (m)	1.83
Integrated Cord Clip	No
USER INTERFACE, ALERTS & CONTROLS	
Diagnostic LED(s)	Yes
LED Indicators	Proper wiring and surge protection working
SURGE / NOISE SUPPRESSION	
AC Suppression Joule Rating	1410
Automatic Shut-Off	No
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
PHYSICAL	
Anti-Microbial Protective Coating	Yes
Color	White
Color (AC Line Cord)	White
Integrated Keyhole Mounting Slots	Yes (Includes flanges)
Material of Construction	Metal
Receptacle Color	White
Shipping Dimensions (hwd / cm)	6.10 x 14.73 x 36.58
Shipping Dimensions (hwd / in.)	2.40 x 5.80 x 14.40



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Shipping Weight (kg)	1.18
Shipping Weight (lbs.)	2.60
Unit Dimensions (hwd / cm)	3.8 x 34.9 x 6.4
Unit Dimensions (hwd / in.)	1.5 x 13.75 x 2.5
Unit Weight (kg)	1.45
Unit Weight (lbs.)	3.20
SPECIAL FEATURES	
Rotatable Outlets	No
CERTIFICATIONS	
Approvals	TUV tested and Listed to UL 60601-1 and UL 60950-1 (USA); TUV tested to CAN/CSA-C22.2 No. 601.1-M90 and 60950-1-03 (Canada)
Patented	Patent# 7,375,939; Patent# 8,339,759
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>