




United Kingdom

T18R

111-91819



T18S – T250XL



Available in a wide range of materials, these cable ties all feature internal serrations allowing for a positive hold onto cable, hose and pipe bundles. The design of the head guarantees a high tensile strength whilst allowing a very low insertion force, this, combined with the bent tail design of many of the ties, ensures a simple and quick installation. Whilst easily installed by hand, manual and pneumatic (for high volume applications) tensioning tools are available to ensure a consistent and safe installation.

For the routing, bundling and securing of cables, pipes and hoses.

Base Data**Application Method**

Quick, simple fixing by hand or with HellermannTyton tensioning tools

Colour

Natural (NA)

Package Content

100

Quantity (Sold Unit / EDP)

100

Quantity per

Bag

Recommended Application Tool

MK20, MK3PNSP2, MK7P, MK7, MK3SP

Logisitic and Packaging**Carton Quantity**

25000

EAN code

4031026107585

Quantity of Europallet

450000

Weight (kg) (Metric)

0.28 kg

Material and Specifications**Flammability**

UL94 V0

Material

Polyamide 6.6 V0 (PA66V0)

Material Shortcut

PA66V0

Operating Temperature (Metric)

-40 °C to +85 °C Continuous, (+105 °C for 500 h)

Product Dimensions**Bundle Diameter max (Imperial)**

.86 "

Bundle Diameter max (Metric)

22

Bundle Diameter min (Metric)

1.5

Length L (Imperial)

4 "

Length L (Metric)

100

Minimum Tensile Strength (N)

80

Width W (Metric)

2.5

© HellermannTyton 2006