

# ISO cylinder DSBC-50-300-PPVA-N3

Part number: 2098975

**FESTO**



## Data sheet

| Feature                                  | Value                                                              |
|------------------------------------------|--------------------------------------------------------------------|
| Piston seal material                     | TPE-U(PU)                                                          |
| Piston rod wiper seal material           | TPE-U(PU)                                                          |
| Cushion piston material                  | POM                                                                |
| Buffer seal material                     | TPE-U(PU)                                                          |
| Material of piston                       | Aluminium-Knetlegierung                                            |
| Nut material                             | Stahl, verzinkt                                                    |
| Flange screws material                   | Stahl verzinkt                                                     |
| Material of bearing                      | POM                                                                |
| Stroke                                   | 300 mm                                                             |
| Piston diameter                          | 50 mm                                                              |
| Piston rod thread                        | M16x1.5                                                            |
| Type code                                | DSBC                                                               |
| Cushioning                               | Pneumatic cushioning, adjustable at both ends                      |
| Mounting position                        | Any                                                                |
| Conforms to standard                     | ISO 15552                                                          |
| Piston rod end                           | External thread                                                    |
| Design                                   | Piston rod<br>Profile barrel<br>Piston                             |
| Position sensing                         | For proximity sensor                                               |
| Symbol                                   | 00991235                                                           |
| Variants                                 | Piston rod at one end                                              |
| Operating pressure                       | 0.4 bar ... 12 bar                                                 |
| Mode of operation                        | Double-acting                                                      |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)         | 2 - Moderate corrosion stress                                      |
| Ambient temperature                      | -20 °C ... 80 °C                                                   |
| Impact energy in the end positions       | 1 J                                                                |
| Cushioning length                        | 22 mm                                                              |
| Theoretical force at 6 bar, retracting   | 990 N                                                              |
| Theoretical force at 6 bar, advancing    | 1178 N                                                             |
| Moving mass at 0 mm stroke               | 365 g                                                              |
| Additional weight per 10 mm stroke       | 56 g                                                               |
| Basic weight with 0 mm stroke            | 1190 g                                                             |
| Additional moving mass per 10 mm stroke  | 25 g                                                               |

| Feature                     | Value                                                   |
|-----------------------------|---------------------------------------------------------|
| Type of mounting            | With internal thread<br>Optionally:<br>With accessories |
| Pneumatic connection        | G1/4                                                    |
| Note on materials           | RoHS-compliant                                          |
| Cover material              | Die-cast aluminum                                       |
| Piston rod material         | High-alloy steel                                        |
| Material of cylinder barrel | Wrought aluminum alloy                                  |