



Air solenoid valve VUVG-LK10-B52-T-M5-1R8L-S

FESTO

Part number: 8042544



Data sheet

| Feature | Value |
|--|--|
| Valve function | 5/2, bistable |
| Lap | Overlap |
| Actuation type | Electrical |
| Valve size | 10 mm |
| Standard nominal flow rate | 195 l/min |
| Pneumatic working port | M5 |
| Operating voltage | 24V DC |
| Operating pressure | 1.5 bar ... 7 bar |
| Design | Piston gate valve |
| Degree of protection | IP65 |
| Type code | VUVG |
| Exhaust air function | With flow control option |
| Sealing principle | Soft |
| Mounting position | Any |
| Manual override | Non-detenting Detenting |
| Type of control | Pilot-controlled |
| Pilot air supply port | Internal |
| Flow direction | Non-reversible |
| Symbol | 00992897 |
| Signal status display | LED |
| Max. switching frequency | 2 Hz |
| Changeover time | 7 ms |
| Duty cycle | 100% |
| Max. positive test pulse with 0 signal | 1600 µs |
| Max. negative test pulse on 1 signal | 3000 µs |
| Coil characteristics | 24 V DC: 0.8 W |
| Permissible voltage fluctuations | +/- 10 % |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Vibration resistance | Transport application test with severity level 1 as per FN 942017-4 and EN 60068-2-6 |
| Shock resistance | Shock test with severity level 1 as per FN 942017-5 and EN 60068-2-27 |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| Temperature of medium | -5 °C ... 50 °C |
| Pilot medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |

| Feature | Value |
|------------------------|--|
| Ambient temperature | -5 °C ... 50 °C |
| Product weight | 57 g |
| Electrical connection | 3-pin Plug M8x1 A-coded as per EN 61076-2-104 |
| Type of mounting | On terminal strip With through-hole |
| Pneumatic connection 2 | M5 |
| Pneumatic connection 4 | M5 |
| Note on materials | Contains paint-wetting impairment substances RoHS-compliant |
| Seals material | HNBR NBR |
| Housing material | Wrought aluminum alloy |