

# GS1AM1

Auxiliary contacts, TeSys GS, 1 C/O, early break, front mounting, for GS1 50-400 A with direct right handle

Product availability : Non-Stock - Not normally stocked in distribution facility



## Main

Range of product	TeSys
Device short name	GS1AM
Product or component type	Auxiliary contact
Contact application	O and I position signalling
Range compatibility	TeSys GS GS1 F fuse-switch disconnectors TeSys GS GS1G fuse-switch disconnectors TeSys GS GS1 J fuse-switch disconnectors TeSys GS GS1 K fuse-switch disconnectors TeSys GS GS1 L fuse-switch disconnectors TeSys GS GS1 N fuse-switch disconnectors TeSys GS GS1Q fuse-switch disconnectors
Contacts type and composition	1 C/O
Contact operation	Early-break
[I <sub>th</sub> ] conventional free air thermal current	16 A 104 °F (40 °C)
[I <sub>e</sub> ] rated operational current	5 A 127 V AC-15 4 A 230 V AC-15 3 A 400/415 V AC-15 2 A 440 V AC-15 12 A 24 V DC-13 2 A 48 V DC-13 0.6 A 110 V DC-13 0.4 A 220 V DC-13

## Complementary

Mechanical durability	1 Mcycles
Electrical durability	30000 cycles AC-15
Switch rated current	50 A 63 A 100 A 125 A 160 A 200 A 250 A 315 A

	400 A
Fuse type	NFC DIN BS
Type of operating handle	Direct right side
Mounting location	Front face
Net weight	0.05 lb(US) (0.023 kg)

### Ordering and shipping details

Category	18402 - WORLD SERVICE PARTS(CONTROL ACCESS)
Discount Schedule	CP10
GTIN	03389110563214
Returnability	No
Country of origin	FR

### Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

### Contractual warranty

Warranty	18 months
----------	-----------