

# GS1AM2

Auxiliary contacts, TeSys GS, 2 C/O, early break, front mounting, for GS1 50-400 A with direct right handle



GS1AM2 has not been replaced. Please contact your customer care center for more information.

! Discontinued

## Main

Range of product	TeSys
Device short name	GS1AM
Product or component type	Auxiliary contact
Contact application	O and I position signalling
Range compatibility	TeSys GS GS1 F fuse-switch disconnecter TeSys GS GS1G fuse-switch disconnecter TeSys GS GS1 J fuse-switch disconnecter TeSys GS GS1 K fuse-switch disconnecter TeSys GS GS1 L fuse-switch disconnecter TeSys GS GS1 N fuse-switch disconnecter TeSys GS GS1Q fuse-switch disconnecter
Contacts type and composition	2 C/O
Contact operation	Early-break
[I <sub>th</sub> ] conventional free air thermal current	16 A 104 °F (40 °C)
[I <sub>e</sub> ] rated operational current	5 A 127 V AC-15 4 A 230 V AC-15 3 A 400/415 V AC-15 2 A 440 V AC-15 12 A 24 V DC-13 2 A 48 V DC-13 0.6 A 110 V DC-13 0.4 A 220 V DC-13

## Complementary

Mechanical durability	1 Mcycles
Electrical durability	30000 cycles AC-15
Switch rated current	50 A 63 A 100 A 125 A 160 A 200 A 250 A 315 A 400 A
Fuse type	NFC

	DIN BS
Type of operating handle	Direct right side
Mounting location	Front face
Net weight	0.08 lb(US) (0.035 kg)

### Ordering and shipping details

Category	18402-WORLD SERVICE PARTS(CONTROL ACCESS)
Discount Schedule	CP10
GTIN	03389110563221
Returnability	No
Country of origin	FR

### Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------