

GS1AN11G

Auxiliary contacts, TeSys GS, 1NC + 1NO, instantaneous, right side mounting, for GS2 with left handle



⚠ Discontinued

GS1AN11G has not been replaced. Please contact your customer care center for more information.

Main

| | |
|--|--|
| Range of product | TeSys |
| Device short name | GS1AN |
| Product or component type | Auxiliary contact |
| Contact application | O and I position signalling |
| Contacts type and composition | 1 NC + 1 NO |
| Contact operation | Instantaneous |
| [I _{th}] conventional free air thermal current | 20 A 104 °F (40 °C) |
| [I _e] rated operational current | 1 A 220 V DC-13 10 A 230 V AC-15 12 A 127 V AC-15 4 A 48 V DC-13 6 A 440 V AC-15 8 A 400/415 V AC-15 1.2 A 110 V DC-13 |

Complementary

| | |
|-----------------------|--|
| Range compatibility | TeSys GS switch-disconnector-fuse |
| Mechanical durability | 30000 cycles |
| Electrical durability | 30000 cycles AC-15 |
| Switch rated current | 200 A 630 A 50 A 125 A 160 A 315 A 400 A 600 A 800 A 100 A 250 A 60 A 1250 A 63 A |
| Fuse type | BS NFC DIN |

| | |
|--------------------------|------------------------|
| Type of operating handle | External left side |
| Net weight | 0.29 lb(US) (0.131 kg) |

Ordering and shipping details

| | |
|-------------------|------------------------------|
| Category | 22640-IEC DISCONNECT-GS1,LK3 |
| Discount Schedule | I11 |
| GTIN | 03389110705874 |
| Returnability | No |
| Country of origin | FR |

Offer Sustainability

| | |
|----------------------------|--|
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|