

FDD / FDFD Series



Insulated Crimp Terminals Metric


Female Push-On



Features:

- Easy cable entry guide which eliminates flared wire strands.
- Bright electroplated finish which prevents oxidation.
- Full compliance to BS4579, IEC352-2, ISO1996.
- A digit is indented above the crimp to verify correct usage.

Fully Insulated Female Push-On



Specifications:

Current ratings	: Quoted at 415 V ac maximum at 32°C.
Temperature range	: -20°C to +85°C.
Insulation	: Coloured Vinyl.
Terminal	: Brass, Copper to BS6017 (1981).
Plating	: Electroplated to BS1872 (1984).
Maximum Electrical Rating	: 75°C 300 Volts.

Crimp Selection Chart

Wire Details	Insulation Colour		
	Red	Blue	Yellow
Wire size in mm ²	0.25 - 1.65	1.04 - 2.63	2.63 - 6.64
Single standard wire size diameter	0.57 - 1.44	1.14 - 1.82	1.82 - 2.89
Equivalent A.W.G.	22 - 16	16 - 14	12 - 10
Equivalent S.W.G.	29 - 17	17 - 13	11 - 6
Suitable metric cables			
Stranded	19/0.15	19/0.3	19/0.45
	13/0.2	7/0.5	44/0.3
	16/0.2	21/0.3	7/0.85
	19/0.2	30/0.25	56/0.3
	14/0.25	19/0.335	65/0.3
	24/0.2	63/0.2	37/0.4
	19/0.25	28/0.3	159/0.2
	32/0.2	35/0.3	84/0.3
	40/0.2	51/0.25	7/1.04
Single	19/0.3	-	-
	1/0.9	1/1.38	1/2.25
	1/1.13	1/1.78	-

Dimensions : Millimetres

AWG = American Wire Gauge.

SWG = Standard Wire Gauge.


Conductor make up metric cables i.e. 19/0.15 = 19 strands of 0.15mm diameter.



FDD / FDFD Series



Insulated Crimp Terminals Metric



Specification Table

Type	W	a	L	C	B	T	Current Rating	Colour	Part Number
Female Push-On	3.2	0.8	19.7	1.7	10.5	0.4	10	Red	FDD1-110(8)
	5.03	0.5							FDD1-187(5)
	4.9								FDD1-187(8)
	6.6	0.8							21.2
	5.03	0.5	19.7	2.3			24	Yellow	FDD2-187(5)
	4.9	0.8							21
	6.6		23.5	3.4					13
Fully Insulated Female Push-On	-	-	-	-	-	-	10	Red	FDFD1-187(8)
	-	-	-	-	-	-			FDFD1-250
	-	-	-	-	-	-	15	Blue	FDFD2-187(8)
	-	-	-	-	-	-			FDFD2-250
	-	-	-	-	-	-	24	Yellow	FDFD5-250
Double Crimp With Sleeve on Barrel	-	-	-	-	-	-	10	Red	FDD1-110(5)

Dimensions : Millimetres



FDD / FDFD Series

Insulated Crimp Terminals Metric



Notes:

International Sales Offices:

**AUSTRALIA – Farnell InOne**

Tel No: ++ 61 2 9645 8888
Fax No: ++ 61 2 9644 7898

**FINLAND – Farnell InOne**

Tel No: ++ 358 9 560 7780
Fax No: ++ 358 9 345 5411

**NETHERLANDS – Farnell InOne**

Tel No: ++ 31 30 241 7373
Fax No: ++ 31 30 241 7333

**SWITZERLAND – Farnell InOne**

Tel No: ++ 41 1 204 64 64
Fax No: ++ 41 1 204 64 54

**AUSTRIA – Farnell InOne**

Tel No: ++ 43 662 2180 680
Fax No: ++ 43 662 2180 670

**FRANCE – Farnell InOne**

Tel No: ++ 33 474 68 99 99
Fax No: ++ 33 474 68 99 90

**NEW ZEALAND – Farnell InOne**

Tel No: ++ 64 9 357 0646
Fax No: ++ 64 9 357 0656

**UK – Farnell InOne**

Tel No: ++ 44 8701 200 200
Fax No: ++ 44 8701 200 201

**BELGIUM – Farnell InOne**

Tel No: ++ 32 3 475 2810
Fax No: ++ 32 3 227 3648

**GERMANY – Farnell InOne**

Tel No: ++ 49 89 61 39 39 39
Fax No: ++ 49 89 613 59 01

**NORWAY – Farnell InOne**

Tel No: ++ 45 44 53 66 66
Fax No: ++ 45 44 53 66 02

**UK – BuckHickman InOne**

++ 44 8450 510 150
++ 44 8450 510 130

**BRAZIL – Farnell-Newark InOne**

Tel No: ++ 55 11 4066 9400
Fax No: ++ 55 11 4066 9410

**HONG KONG – Farnell-Newark InOne**

Tel No: ++ 852 2268 9888
Fax No: ++ 852 2268 9899

**PORTUGAL – Farnell InOne**

Tel No: ++ 34 93 475 8804
Fax No: ++ 34 93 474 5288

**UK – CPC**

++ 44 8701 202 530
++ 44 8701 202 531

**CHINA – Farnell-Newark InOne**

Tel No: ++86 10 6238 5152
Fax No: ++86 10 6238 5022

**IRELAND – Farnell InOne**

Tel No: ++ 353 1 830 9277
Fax No: ++ 353 1 830 9016

**SINGAPORE – Farnell-Newark InOne**

Tel No: ++ 65 6788 0200
Fax No: ++ 65 6788 0300

**EXPORT – Farnell InOne**

Tel No: ++ 44 8701 200 208
Fax No: ++ 44 8701 200 209

For enquiries from all other markets

**DENMARK – Farnell InOne**

Tel No: ++ 45 44 53 66 44
Fax No: ++ 45 44 53 66 06

**ITALY – Farnell InOne**

Tel No: ++ 39 02 93 995 200
Fax No: ++ 39 02 93 995 300

**SPAIN – Farnell InOne**

Tel No: ++ 34 93 475 8805
Fax No: ++ 34 93 474 5107

**ESTONIA – Farnell InOne**

Tel No: ++ 358 9 560 7780
Fax No: ++ 358 9 345 5411

**MALAYSIA – Farnell-Newark InOne**

Tel No: ++ 60 3 7873 8000
Fax No: ++ 60 3 7873 7000

**SWEDEN – Farnell InOne**

Tel No: ++ 46 8 730 50 00
Fax No: ++ 46 8 83 52 62

<http://www.farnellinone.com>

<http://www.buckhickmaninone.com>

<http://www.cpc.co.uk>

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2004.

