

## Fiber optic cable - FOC-LC:PA-ST:PA-OM2:D01/1 - 1115588

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Multi-mode OM2 duplex jumper, LC-ST, UPC polishing, length 1 m

### Your advantages

- ✓ Glass fiber optical, 8-shaped FO cable jumper
- ✓ Indoor use, suitable for fiber optics distribution and termination devices
- ✓ Made of halogen-free flame retardant material, RoHS compliant



### Key Commercial Data

|                      |   |
|----------------------|---|
| Packing unit         | 1   |
| GTIN                 | <br>4 063151 036386 |
| GTIN                 | 4063151036386   |
| Custom tariff number | 85447000  |

### Technical data

#### Dimensions

|                 |        |
|-----------------|--------|
| Length of cable | 1.00 m |
|-----------------|--------|

#### Ambient conditions

|   |                  |
|---|------------------|
| Ambient temperature (storage/transport) | -20 °C ... 60 °C |
|---|------------------|

#### General

|                             |                                 |
|-----------------------------|---------------------------------|
| Standards/regulations       | IEC 61300-3-4 RL: IEC 61300-3-6 |
| Insertion/withdrawal cycles | ≥ 500                           |

#### Material

|  |    |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

#### Cable

|                    |                      |
|--------------------|----------------------|
| Cable type         | Multimode fiberglass |
| Cable abbreviation | I-V(ZN)H             |

## Fiber optic cable - FOC-LC:PA-ST:PA-OM2:D01/1 - 1115588

### Technical data

#### Cable

|                          |   |
|--------------------------|---|
| Cable structure          | Figure 8 cable                                  |
| External sheath, color   | orange  |
| External cable diameter  | 2.00 mm   |
| Cable weight             | 5.30 kg/km                                      |
| Outer sheath, material   | LSZH  |
| Standards/specifications | IEC 61300-3-4 RL: IEC 61300-3-6                 |
| Halogen-free             | According to IEC 60754-2                        |
| Resistance to oil        | Not resistant to oil, gasoline, acids, and lyes |
| Concentration of fumes   | in accordance with IEC 61034                    |

#### Standards and Regulations

|  |   |
|--|---|
| Standards/specifications               | IEC 61300-3-4 RL: IEC 61300-3-6                 |
| Concentration of fumes                 | in accordance with IEC 61034                    |
| Resistance to oil                      | Not resistant to oil, gasoline, acids, and lyes |
| Halogen-free                           | According to IEC 60754-2                        |
| Behavior in fire                       | No corrosive or toxic fumes                     |
| Flammability rating according to UL 94 | V0  |

#### Environmental Product Compliance

|            |   |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50 years  |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 8.0 | 27061801 |
| eCl@ss 9.0 | 27061003 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 5.0 | EC001578 |
|----------|----------|