Fray Resistant, Flame Retardant, Expandable Sleeving





Features

- · Black with white tracer
- · Fray resistant, can be cut with scissors
- Rated to 125°C
- Low temperature flexibility to -70°C
- VW-1
- F.A.R. Part 25
- · Does not trap heat or humidity
- Rot-free
- · Self-fitting over many shapes and sizes

Performance Data

Property	Test Method	Value
Filament Diameter	-	0.01"
Melt Temperature	ASTM D-2117	239°C
Low Temperature Flexibility	MIL-DTL-23053E	-70°C
Flammability	UL 1441	VW-1
Flammability	F.A.R. Part 25	Pass
Smoke Density	ASTM E-1354	D _{mc} = 5.72
Copper Corrosivity	MIL-I-23053	No Effect

Specification Table

Part Number	Nominal Dia. (Inches)	Maximum Dia. (Inches)	Spool Length (Feet)
SPC12221	1/8	1/4	100
SPC12222	1/4	7/16	100
SPC12223	3/8	1/2	100
SPC12224	1/2	3/4	100
SPC12225	3/4	1-1/4	50
SPC12226	1-1/4	1-3/4	50
SPC12227	1-3/4	2-3/4	25
SPC12228	2	3-1/2	25
SPC12229	2-1/2	4-1/2	25

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

